



Product Data Sheet

1055-N

1055 series

The Sentrol 1055 series are ideal for mounting in aluminum door and window tracks and sliding glass door tracks. Recess mount in wood doors and windows. The recessed magnetic contact is only 0.64 cm in diameter. Adhesive required to security mounting.

Durability and dependability

The Sentrol high performance magnetic contacts have been designed to facilitate installation and ensure durability and dependability. Most are conservatively rated at 10,000,000 cycles, guaranteeing a long life. Every reed connection is hand soldered and each magnetic contact is tested before they leave the factory, 100% of the time.

High quality components and materials

Reed legs are plated with rhodium or ruthenium, and hermetically sealed in dry nitrogen. This offers superior protection against sticking and provides a moisture free environment therefore preventing corrosion.

Características Standard

- Perfect for window screen protection
- Versatile compact size
- Attractive, added security of recessed installation

1055-N

Especificações Técnicas

Gap distance (max)	13 mm
Connections	30 cm wire leads
Contact	NC
Supervised loop	No
Dimensions (Ø x L)	
Contact	Ø 6 x 29 mm
Magnet	Ø 6 x 32 mm
Color	White

Como Encomendar

Referência	Descrição
1055-N	Recessed mount magnetic contact with bare magnet, white

