

ACCESS CONTROL PUSH BUTTONS

12 TO 24 VDC
SPDT SWITCH
STAINLESS STEEL



TECHNICAL SPECS

SWITCH VOLTAGE
125 / 250 VAC

SWITCH CURRENT
10A

HIGH VOLT BULB
15-24 VDC Input
0.06A Current

LOW VOLT BULB
12-14 VDC Input
0.19A Current

MATERIAL
Stainless Steel Faceplate
Plastic Transparent Push Button

DIMENSIONS
2¾" x 4½" x ¾"
(70mm x 114mm x 9.5mm)

BUTTON DIMENSIONS
1" x 1"
(25.4mm x 25.4mm)

COMPATIBILITY
Most Single Gang Boxes

Innovation
Quality
Service

The brightly lit push button is mounted in a rugged stainless steel single gang plate to offer an attractive alternative for any indoor application.

- Available with either white on blue standard handicap logo or black on green "PUSH TO EXIT" illuminated button
- Interchangeable light bulb supplied
- Accommodates 12 VDC to 24 VDC input voltage
- The momentary push button switch provides for a NO / NC contact
- Tamper proof mounting screws are included for added security
- Ideal for access control, request to exit, and security applications

WWW.BEASENSORS.COM

BEA Inc.
RIDC Park West
100 Enterprise Drive
Pittsburgh, PA 15275-1213

PHONE: 1 800.523.2462
FAX: 1 888.523.2462

BEA West
Arrow Highway Corporate Center
190 E. Arrow Hwy, Suite A
San Dimas, CA 91773-3314

PHONE: 1 800.523.2462
FAX: 1 888.523.2462

BEA Latin America
Mexico / Caribbean
190 E. Arrow Hwy, Suite A
San Dimas, CA 91773-3314

PHONE: 1 800.711.1398
FAX: 1 888.523.2462