

Description: 18 AWG 6/C OAS CM-CL2
Specifications: UL Standards 13 & 444; NEC Articles 725 & 800

Construction:

Conductor 18 AWG 19/0.0092" Stranded Bare Copper
Insulation Polypropylene
Insulation Thickness 0.006" nom.
Insulation Colors Blk,Wht,Red,Grn,Blu,Brn
Insulation Diameter 0.058 nom.
Lay Length 3.5" nom.
Drain Wire 22 AWG 7/30 Tinned Copper
Shield .001" Thick Aluminum/Mylar

Jacket PVC
Jacket Thickness 0.016" nom.
Outside Diameter 0.210" nom.
Legend (Ink Print) **HONEYWELL P/N 1216 6C18 SHIELDED 3038058 (ETL) CL2 OR CM C(ETL)US
SUN RES (RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E
F 1 2 3 4 5 6 7 8 9**

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 35 pf/ft nom.
Impedance 42 Ohms nom.
DC Resistance 6.5 Ohms/M' at 20°C
Flame Rating UL 1685 Vertical Tray