DATA SHEET

COD. 1252

SIMPLEBUS AMPLIFIER FOR ADDITIONAL UNITS IN PARALLEL

Up to 16 monitors/telephones can be connected with the same address, in order to ring at the same time. By adding additional power supplies, all the monitors they can also turn ON simultaneously after a call. Art. 1252 does not provide power to the monitor. Dimensions 6 DIN modules. Power supply 120-230 Vac.



General info

	Product height (mm):	90	
	Product width (mm):	105	
	Product depth (mm):	61	
	Operating temperature (°C):	0/30	
	EAN product code:	8023903201093	
	Intrastat code:	85176910	
Com	patibility		
	Simplebus Top system:	Yes	
	Simplebus 2 system:	Yes	
Mour	nting/Installation		
	Wall-mounted:	Yes	
	Surface-mounted:	Yes	
	DIN rail mounted:	Yes	
	DIN modules (no.):	6	
Audi	o/video specifications		
	Audio system:	Yes	
	Audio/video system:	Yes	
Flect	rical specifications		
21000	Maximum current absorption (mA):	200	
21000	Maximum current absorption (mA):	200	
	Maximum current absorption (mA):	200	



The technical specifications are subject to variations without warning

DATA SHEET

Single pack width (mm):	111	
Single pack weight (Kg):	0,884	
Single pack depth (mm):	100	
Single pack volume (dm3):	0,738	



The technical specifications are subject to variations without warning