

MASTER APARTMENT GATEWAY FOR VIP SYSTEM

Apartment gateway in master version (does not require presence of door entry monitors). Allows the operation of door entry monitor system via tablets and smartphones using the Comelit ViP App, which can be downloaded free of charge. This function can be used locally via a Wi-Fi network or on portable devices using 3G (or higher) networks; automatic switching between Wi-Fi and 3G networks according to availability. In all cases, the gateway should be connected to an ASDL router or another device guaranteeing local Wi-Fi and mobile 3G connectivity. Depending on bandwidth limitations, the gateway can serve up to 15 appliances (including door entry monitors, smartphones, tablets and PCs) with 4 simultaneous audio/video streams. It also allows "intercom" communication between all of the 15 devices served. The gateway is equipped with 1 Ethernet port for ViP system riser input, 1 PoE port, 2 PoE ports (can be set to non-PoE) and 1 non-PoE port. It is also equipped with an input for the power supply. Dimensions: 70x90x62 mm (4 DIN modules).



General info

Product height (mm):	62
Product width (mm):	70
Product depth (mm):	90
Operating temperature (°C):	-5/50

Compatibility

Vip system:	Yes
-------------	-----

Mounting/Installation

DIN rail mounted:	Yes
DIN modules (no.):	4

Connectivity

Ethernet ports:	Yes
-----------------	-----

Packaging

Single pack height (mm):	76
Single pack width (mm):	86
Single pack weight (Kg):	0,164
Single pack depth (mm):	96
Single pack volume (dm3):	0,627