

# DATA SHEET

## COD. 1622

### SIMPLEBUS AUDIO SPEAKER UNIT FOR IKALL ENTRANCE PANEL.

Audio speaker unit for Simplebus system, complete with terminal block and digital audio management system with Eco-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and DIP SWITCH with 8 positions for programming calls to users. 33Vdc power supply via special power supply unit art. 1595. On-board electronic lock-release function (3A), plus C, NC, NO 10A relay contacts. For use in modules Art. 33400, 33401 and 33402. Dimensions: 47x2.2x1.57. Compatible with all SBTOP functions and products. Allows call addressing for up to 120000 users. Timed lock-release input and door open indication.



#### Functions

Key button function:	Yes
Loudspeaker volume control:	Yes
Microphone volume control:	Yes

#### General info

Product height (mm):	55
Product width (mm):	104
Product depth (mm):	35
Operating temperature (°C):	-25/55
EAN product code:	8023903208917
Intrastat code:	85176910

#### Compatibility

Simplebus Top system:	Yes
Simplebus 2 system:	Yes

#### Audio/video specifications

Audio system:	Yes
Audio/video system:	Yes

#### Electrical specifications

Maximum current absorption (mA):	200
----------------------------------	-----

#### Packaging

Single pack height (mm):	53
Single pack width (mm):	110

The technical specifications are subject to variations without warning

## DATA SHEET

Single pack weight (Kg):	0,193
Single pack depth (mm):	94
Single pack volume (dm3):	0,548

The technical specifications are subject to variations without warning