## **DATA SHEET**

## **COD. 1622VC**

## COLOR REMOTE CAMERA INPUT MODULE FOR IKALL ENTRANCE PANEL.

Module which allows modulation and transmission of the color video signal on the riser. On input it has the composite video signal of a color camera. Complete with microprocessor and DIP SWITCH with 8 positions for programming calls to users. 33Vdc power supply via special power supply unit Art. 1595. Onboard electronic lock-release function (3A), plus C, NC, NO 10A relay contacts. For use in modules Art. 33400, 33401 and 33402. Dimensions: 4?x2.2?x1.5?. Compatible with all SBTOP functions and products. Allows call addressing for up to 120000 users. Timed lock-release input and door open indication.



DDE function:	Yes
nctions	
Key button function:	Yes
Loudspeaker volume control:	Yes
Microphone volume control:	Yes
eneral info	
Product height (mm):	55
Product width (mm):	104
Product depth (mm):	35
Operating temperature (°C):	-25/55
EAN product code:	8023903208931
Intrastat code:	85176910
ompatibility	
	Yes
Simplebus Color system:	res
idio/video specifications	
Audio system:	No
Audio/video system:	Yes
ectrical specifications	
	400
Maximum current absorption (mA):	
Maximum current absorption (mA):	
Maximum current absorption (mA):  ckaging	



## **DATA SHEET**

Single pack width (mm):	117	
Single pack weight (Kg):	0,318	
Single pack depth (mm):	160	
Single pack volume (dm3):	0,562	

