George Risk Industries

(800) 523-1227

Home Products About GRI Contact GRI Where to Buy Testimonials What's New!

20F Series 3/8" Flanged Recessed Switch Sets




20F-12Recessed Switch Set




20 OF-12 Recessed Switch Set

- Lifetime Warranty
- Colors: White, Brown, Gray or Black
- UL and ULC Approved
- Available in Closed Loop, Open Loop, SPDT and DPDT
- Standard 12" Leads
- Longer Leads, Zip Cord or Jacketed Cable on Request
- Built-in E.O.L. Resistors and Diodes Available on Request
- Switches or Magnets are Available Separately
- Round or Oval Flange Available
- Standard Gap 1/2"+
- Wide Gap 1"+
- Extra Wide Gap 1 1/2"+
- Supervisory Loops Available

The 20F and 20 OF Series are a flush mount design that enable the installer to combine the security of a screw mount flanged switch with the concealment of a press fit switch. They have been used in hollow aluminum frames where inadequate material depth will not reliably retain a press fit switch and in holes that have been drilled or have somehow become slightly oversized. They are available in 1/2" to 1 1/2" gap. Mounting hardware is provided.





20 OF-12 Recessed Switch Set

RECESSED 3/8" FLANGED SWITCH SET



20F/20 OF SERIES (9) (6)

- ◆ Recessed Magnetic Contact
- ◆ Round or Oval Screw Down Flange ◆ 12" Leads #22AWG Leads
 - ◆ Longer Leads, Zip Cord or Jacketed Cable Upon Request
- ◆ Hermetically Sealed ◆ Plated Contacts Resist Sticking or Freezing
 - ◆ Mounting Hardware Included
 - ◆ Built-in E.O.L. Resistors and Diodes Upon Request
 - ◆ Switches and Magnets Available Separately
 - ◆ Colors: White, Brown, Gray, Black
 - ◆ Lifetime Warranty



20F-12



20OF-12

PART NUMBERS:	Closed Loop	Open Loop	SPDT	DPDT
Standard	20F-12	30F-12	40F-12	45F-12
Gap 1/2"+	20 OF-12	30 OF-12	40 OF-12	45 OF-12
Wide Gap	20F-12WG	30F-12WG	40F-12WG	45F-12WG
Gap 1"+	20 OF-12WG	30 OF-12WG	40 OF-12WG	45 OF-12WG
Extra Wide Gap	20F-12XWG	30F-12XWG	40F-12XWG	45F-12XWG
Gap 1 1/2"+	20 OF-12XWG	30 OF-12XWG	40 OF-12XWG	45 OF-12XWG

GEORGE RISK INDUSTRIES, INC. GR.I. PLAZA KIMBALL, NE 69145



TOLL-FREE 1-800-445-5218 TOLL-FREE 1-800-523-1227

(308) 235-4645

FAX (308) 235-3561


E-MAIL: grisales@megavision.com WEB SITE: www.grisk.com



RECESSED 3/8" FLANGED SWITCH SET

INSTALLATION APPLICATIONS:

The 20F and 20 OF series are a flush mount design that enable the installer to combine the security of a screw mount flanged switch with the concealment of a press fit switch. They have been used in hollow aluminum frames where inadequate material depth will not reliably retain a press fit switch and in holes that have been drilled or have somehow become slightly oversized. They are available in 1/2 inch to 1 1/2 inch gap and mounting hardware is provided.



GRI products meet or exceed these minimum general specifications:

on products meet of exceed these minimum general specifications.								
LOOP TYPE	ELECTRICAL CONFIG.	REED FORM	MAXIMUM INITIAL CONTACT RESISTANCE	MAXIMUM CONTACT RATING	MAXIMUM SWITCHING VOLTAGE	MAXIMUM SWITCHING CURRENT		
			(Ω)	(W)	(VDC)	(A)		
Closed	N/O	А	.150	10	200	.500		
Closed	N/O	Α	.150	10	200	.500		
Closed	N/O	Α	.150	10	200	.500		
Closed	N/O	Α	.150	10	200	.500		
Closed	N/O	Α	.150	10	200	.500		
Closed	N/O	Α	.150	10	200	.500		
Open	N/C	В	.140	5	175VDC	.250		
Open	N/C	В	.140	5	175VDC	.250		
Open	N/C	В	.140	5	175VDC	.250		
Open	N/C	В	.140	5	175VDC	.250		
Open	N/C	В	.140	5	175VDC	.250		
Open	N/C	В	.140	5	175VDC	.250		
Open/Closed	SPDT	С	.140	5	175VDC	.250		
Open/Closed	SPDT	С	.140	5	175VDC	.250		
Open/Closed	SPDT	С	.140	5	175VDC	.250		
Open/Closed	SPDT	С	.140	5	175VDC	.250		
Open/Closed	SPDT	С	.140	5	175VDC	.250		
Open/Closed	SPDT	С	.140	5	175VDC	.250		
Open/Closed	DPDT	Cx2	.140	5	175VDC	.250		
Open/Closed	DPDT	Cx2	.140	5	175VDC	.250		
Open/Closed	DPDT	Cx2	.140	5	175VDC	.250		
Open/Closed	DPDT	Cx2	.140	5	175VDC	.250		
Open/Closed	DPDT	Cx2	.140	5	175VDC	.250		
	Closed Closed Closed Closed Closed Closed Closed Open Open Open Open Open Open Open Open	LOOP TYPE Closed N/O Open N/C Open/Closed SPDT Open/Closed SPDT Open/Closed SPDT Open/Closed SPDT Open/Closed SPDT Open/Closed DPDT Open/Closed DPDT Open/Closed DPDT Open/Closed DPDT Open/Closed DPDT	LOOP TYPE Closed N/O Closed N/O Closed N/O Closed N/O A Closed N/O Closed N/O Closed N/O A Closed N/O Closed N/O A Closed N/O B Open N/C B Open Closed SPDT C Open/Closed DPDT Cx2 Open/Closed DPDT Cx2 Open/Closed DPDT Cx2	LOOP TYPE CONFIG. FORM INITIAL CONTACT RESISTANCE (Ω)	LOOP TYPE ELECTRICAL CONFIG. REED FORM FORM MAXIMUM INITIAL CONTACT RESISTANCE (Ω) MAXIMUM CONTACT RATING (W) Closed N/O A .150 10 Open N/C B .140 5 Open/Closed SPDT C .14	LOOP TYPE ELECTRICAL CONFIG. REED FORM MAXIMUM INITIAL CONTACT RESISTANCE MAXIMUM CONTACT RATING (VDC) MAXIMUM SWITCHING VOLTAGE (VDC) Closed N/O A .150 10 200 Open N/C B .140 5 175VDC Open N/C B .140 5 175VDC Open N/C B .140 5 175VDC Open/Closed		

WARRANTY:

Lifetime warranty against workmanship, material and factory defects.

CONTACT YOUR G.R.I. DISTRIBUTOR OR CALL:

GEORGE RISK INDUSTRIES, INC. GR.I. PLAZA KIMBALL, NE 69145



TOLL-FREE 1-800-445-5218 TOLL-FREE 1-800-523-1227 (308) 235-4645 FAX (308) 235-3561 E-MAIL: grisales@megavision.com

WEB SITE: www.grisk.com