


LCN 2810 SERIES



The 2810 SENIOR SWING by LCN is an ADA door operator that is a two-in-one swing door operator. SENIOR SWING operator when activated, opens doors automatically for wheelchair access, yet allows for manual operation for regular pedestrian traffic.

- ▶ **Push 'N Go** permits non-switch activation
- ▶ **Power Boost** provides additional latching force
- ▶ **Electromechanical unit** with microprocessor control
- ▶ **Meets International Building Code requirements and ANSI A156.19**
- ▶ **UL approved for fire doors**

- ▶ 2810 series operator is shipped with motor gearbox, control box, arm, bottom pivot, header, and mounting hardware. Actuators available separately, see page 121.
- ▶ Single door, overhead concealed.
- ▶ Meets ADA, requirements (power mode only).
- ▶ Handed product.
- ▶ 36" header length is standard. Specify length 33" to 49" max.
- ▶ Double door header available up to 98", specify length 49" to 98" max. Consult factory regarding this option.
- ▶ Fixed or breakaway stop available with center pivot arm.
- ▶ Adjustable hold open period of 1 to 32 seconds in automatic or manual mode.

2810 Series is fully compliant with UL 325 & UL 1998 and meets the provisions of ANSI A156.19. The 2810 Series is UL listed for fire-rated applications. The 2810 Series also meets the provisions of the Americans with Disabilities Act.

MOUNTING					HANDING			FINISH		COVER		ARM FUNCTION		
<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>				
SURFACE MOUNT SINGLE DOOR					HANDED			METAL		STANDARD (SINGLE)		REGULAR (DOUBLE)		
SURFACE MOUNT SIMULTANEOUS PAIR					NON-HANDED			STANDARD ANODIZED		REGULAR (DOUBLE)		DOUBLE EGRESS (PUSH/PULL)		
CONCEALED SINGLE DOOR					STANDARD ANODIZED			CUSTOM ANODIZED		OFFSET PIVOT ARM		CENTER PIVOT ARM		
CONCEALED SIMULTANEOUS PAIR					CUSTOM PAINT			MATERIAL		OFFSET PIVOT ARM		CENTER PIVOT ARM		
CONCEALED INDEPENDENT PAIR					CUSTOM PAINT			MATERIAL		OFFSET PIVOT ARM		CENTER PIVOT ARM		


AVAILABLE
 NOT AVAILABLE

LCN 2810 SERIES

MOUNTING DETAILS


CONCEALED SINGLE DOOR (CENTER PIVOT, EMERGENCY BREAKOUT, PULL) MOUNTING

Minimum header length 36".



CONCEALED SINGLE DOOR (CENTER PIVOT, FIXED STOP, PUSH) MOUNTING

Minimum header length 36".



MAXIMUM OPENING


Template allows 90 degree power opening and 90 degree manual opening.

Special Templates

Customized installation templates or products may be available to solve unusual applications. Contact LCN for assistance.

- ▶ **Head Frame** minimum 36" (L) x 5 3/4" (H) x 4 1/2" (W) " (914 mm x 146 mm x 114 mm).
- ▶ **Top Rail** minimum 2" (51 mm).
- ▶ **Opening & Closing Time** are variable by adjustments to the electronic control box. Maximum hold open time adjustable up to approximately 32 seconds.
- ▶ **Door Stop** required for each door panel.
- ▶ **System Diagram** see "AUTOMATIC OPERATORS" section pages 52-54 for typical system wiring and page 55 for electrical data.
- ▶ Please consult your local SSC representative or LCN for assistance with specific installations and material requirements.

LCN 2810 SERIES



CONCEALED SINGLE DOOR (OFFSET PIVOT OR BUTT HINGE, SLIDE ARM, PUSH) MOUNTING

Minimum header length 33".

Installations require bottom pivot and two intermediate pivots.

- ▶ **Head Frame** minimum 33" (L) x 5 3/4" (H) x 4 1/2" (W) " (838 mm x 146 mm x 114 mm).
- ▶ **Top Rail** minimum 2" (51 mm).
- ▶ **Opening & Closing Time** are variable by adjustments to the electronic control box. Maximum hold open time adjustable up to approximately 32 seconds.
- ▶ **Door Stop** required for each door panel.
- ▶ **System Diagram** see "AUTOMATIC OPERATORS" section pages 52-54 for typical system wiring and page 55 for electrical data.
- ▶ Please consult your local SSC representative or LCN for assistance with specific installations and material requirements.

MAXIMUM OPENING

Template allows 90 degree power opening and 90 degree manual opening.

Special Templates


Customized installation templates or products may be available to solve unusual applications. Contact LCN for assistance.

LCN 2810 SERIES

MOTOR GEARBOX

MOTOR GEARBOX (STANDARD FORCE) – SENIOR SWING, 2810-3454


Driving mechanism for operator. Provides 15lbs opening force. Handed.



MOUNTING BRACKET

MOUNTING BRACKET – 3 3/4", 2810-375

Motor gearbox mounting bracket for 3 3/4" center, offset pivot, butt hinge installations. Front bracket.




MOUNTING BRACKET – 2 3/4", 2810-275

Motor gearbox mounting bracket for 2 3/4" center pivot installations. Front bracket.

REAR MOUNT BRACKET, 2810-3018


Motor gearbox mounting bracket. Rear bracket.



CONTROL BOXES

CONTROL BOX- SENIOR SWING, 2810-3462


Electronic controlling device for Senior Swing.



HEADERS


Header, 2810-3572HL

Standard, mounting header. Single door, single operator. Specify length 30" to 49" maximum.



Header, 2810-3572DD


Standard, mounting header. Double door, single operator. Specify length 49" to 98" maximum.



END CAPS

HEADER END CAPS, 2810-334

End cap with openings for wiring.




ARMS

CENTER PIVOT ARM, 2810-3077CP

(CENTER PIVOT INSTALLATIONS ONLY)


Used with overhead concealed operators and center pivoted doors.



OFFSET PIVOT ARM, 2810-3077OP

(OFFSET PIVOT OR BUTT HUNG INSTALLATIONS ONLY)

Handed arm. Used with overhead concealed operators.




LCN 2810 SERIES

CHANNELS

CONCEALING CHANNEL, 2810-3072


Used to conceal arm in overhead concealed applications. For offset pivot and butt hinges installations. If ordering separately specify length and hand.



SLIDE CHANNEL, 2810-168

(OFFSET PIVOT or BUTT HINGE INSTALLATIONS ONLY)


Mounts in concealing channel. Allows arm to slide.



INSTALLATION ACCESSORIES

DOOR STOP BREAKAWAY, 2810-384B

Allows in swinging door to swing out in case of emergency (Pull installations). For center pivoted installations only.




DOOR STOP FIXED, 2810-384F

Prevents out swinging door from swinging in (Push installations). For center pivoted installations only.


FILLER PLATE BLANK, 2810-12

Completes length of header box.




SPINDLE PLATE – 2 3/4", 2810-11A

Hides bottom of motor gearbox. Completes header box. Cutout allows for motor gearbox shaft. For 2 3/4" offset pivot/butt hinge installations.



SPINDLE PLATE – 3 3/4", 2810-11B


Hides bottom of motor gearbox. Completes header box. Cutout allows for motor gearbox shaft. For 3 3/4" center pivot installations.



PIVOTS

BOTTOM PIVOT ASSEMBLY, 2810-3107

Includes pivot body, pivot post and bottom pivot plate. For overhead concealed, center pivoted installations. Includes; 2810-107, 2810-110 and 2810-117.



PIVOT BODY, 2810-107

Bottom pivot body for center pivoted installations.

PIVOT POST, 2810-110

Connects pivot body to bottom pivot plate for center pivoted installations.

BOTTOM PIVOT PLATE, 2810-117


Applied to floor for center pivoted installations.

LCN 2810 SERIES

TABLE OF SIZES

→ Indicates recommended range of door width for operator.
 Note: For all Senior Swing Series
 Single Door - Width per leaf 36" minimum, 48" maximum

DOOR WIDTH



HOW-TO-ORDER 2810 SERIES OPERATORS

1. SELECT INSTALLATION TYPE

2811

2. ARMS

- Standard 3 3/4" (Offset pivoted) Arm (3077OP)
- Standard 2 3/4" (Center pivoted) Arm (3077CP)
- Standard 3 3/4" (Center pivoted) Arm (3077CP)

3. SPECIFY HAND

- RH
- LH

4. SPECIFY FINISH.

- Standard Anodized Finish _____
Aluminum or Dark Bronze

Operator will be shipped with:

- STANDARD MOTOR GEARBOX (SF)
 - STANDARD CONTROL BOX (SC)
 - 36" HEADER (36HL)
 - 2 3/4" PIVOT POINT
 - WOOD and MACHINE SCREW PACK
- Unless options listed below are selected.*

OPERATOR OPTIONS

HEADER

- HL__ (Specify length 33" to 49" offset pivot)
- HL__ (Specify length 36" to 49" center pivot)
- DD__ (Specify length 49" to 98")

STOPS*

- Positive Mechanical Stop (POS)
- Panic Breakaway Stop (BKY)

**Available with Center Pivoted installations only.*

SPECIAL TEMPLATE

- ST-_____