


DATA SHEET

COD. **3072B**

SIMPLEBUS DIGITAL DIRECTORY MODULE, VANDALCOM SERIES

Made using a double 2.5 mm stainless steel plate, complete with 4 backlit stainless steel buttons and 32-character alphanumeric display. Stores up to 1000 usernames. 2 search buttons are used to scroll through the names. Once the desired name is displayed, simply press the call button. User programming is easy, thanks to programmer art. 1230 or PC software art. 1231/6D. Dimensions: 106x106x56 mm. From IR10 it is compatible with all SBTOP products and functions. It can be used for the call addressing of up to 120000 users.



Main specifications

Backlighting colour: **LED GREEN**

Software/firmware specifications

No. user codes: **1500**

No. of storable users: **1500**

Hardware specifications

Vandal Resistant IK: **Yes**

Customisable housing: **No**

DDE function: **No**

Total buttons: **4**

Sensitive Touch technology: **No**

Functions

Key button function: **No**

General info

Product height (mm): **106**

Product width (mm): **106**

Product depth (mm): **56**

Product colour: **GREY**

Operating temperature (°C): **-25/55**

Intrastat code: **85176920**

Compatibility

Simplebus Top system: **Yes**

DATA SHEET

Simplebus Color system:	Yes
-------------------------	-----

Simplebus 2 system:	Yes
---------------------	-----

Mounting/Installation

Flush-mounted:	Yes
----------------	-----

Wall-mounted:	Yes
---------------	-----

Surface-mounted:	Yes
------------------	-----

Audio/video specifications

Display resolution (H x V):	16x2 characters
-----------------------------	-----------------

Audio system:	Yes
---------------	-----

Audio/video system:	Yes
---------------------	-----

Type of display:	Alphanumeric
------------------	--------------

Connectivity

Type of connections/ports:	RS232, RS485, INFRARED
----------------------------	------------------------

Infrared port:	Yes
----------------	-----

RS232 ports:	1
--------------	---

RS485 ports:	1
--------------	---

Electrical specifications

Maximum current absorption (mA):	100
----------------------------------	-----

Packaging

Single pack height (mm):	88
--------------------------	----

Single pack width (mm):	113
-------------------------	-----

Single pack weight (Kg):	0,747
--------------------------	-------

Single pack depth (mm):	111
-------------------------	-----

Single pack volume (dm3):	1,104
---------------------------	-------