

Description: 22 AWG 6/C STR OAS CMP-CL2P
Specifications: UL Standards 13, & 444; NEC Article 725

Construction:

Conductor 22 AWG 7/30 Bare Copper
Insulation Plenum PVC
Insulation Thickness 0.007" nom.
Insulation Colors Blk,Red,Wht,Grn,Brn,Blu
Insulation Diameter 0.044 nom.
Lay Length 2.5" nom.
Drain Wire 24 AWG 7/32 TC
Shield 0.001" Thick Aluminum/Mylar

Jacket Plenum PVC
Color Natural
Jacket Thickness 0.015" nom.
Outside Diameter 0.166" nom.
Legend (Ink Print) HONEYWELL P/N 3206 6C22 SHIELDED 3038058 (ETL) CL2P OR CMP C(ETL)US FT6
(RoHS) W/O# XXXXXX-XXXXXX XXXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 50 pf/ft nom.
Impedance 40 Ohms nom.
DC Resistance 16.6 Ohms/M' at 20°C
Flame Rating UL 910, NFPA 262, CSA FT6