

### DIGITAL CALL MODULE COMPLETE WITH ELECTRONIC NAME DIRECTORY

Complete with 128X64 dot graphic LCD display, keypad with 16 pushbuttons illuminated from the rear with blue LED's. Also operates as coded electronic key. It is complete with electronic name directory, which stores 400 user names. Name scrolling is carried out by using two search pushbuttons or by entering the initials of the name. Once the desired user name is displayed, simply press the call pushbutton. It is also possible to send the call by entering the user code directly. User programming is carried out in a simple way using programmer Art. 1230 or by means of the software for PC Art. 1249/A or 1249/B. Dimensions: 4.4?x7.1?x1.6?



#### Main specifications

Backlighting colour: LED BLUE

#### Software/firmware specifications

No. user codes: 1000

No. of storable users: 1000

#### Hardware specifications

Vandal Resistant IK: No

Customisable housing: No

DDE function: No

Total buttons: 16

Sensitive Touch technology: No

#### Functions

Key button function: Yes

#### General info

Product height (mm): 180

Product width (mm): 112

Product depth (mm): 40

Product colour: GREY

Operating temperature (°C): -25/55

EAN product code: 8023903118759

Intrastat code: 85176920

#### Compatibility

Simplebus Top system: Yes

# DATA SHEET

Simplebus Color system:	Yes
Simplebus 2 system:	Yes

## Mounting/Installation

Flush-mounted:	Yes
Wall-mounted:	Yes
Surface-mounted:	Yes

## Audio/video specifications

Display size (inches):	3
Display resolution (H x V):	128x64 DOTS
Audio system:	Yes
Audio/video system:	Yes
Type of display:	LCD

## Connectivity

Type of connections/ports:	RS232, RS485, INFRARED
Infrared port:	Yes
RS232 ports:	1
RS485 ports:	1

## Electrical specifications

Maximum current absorption (mA):	100
----------------------------------	-----

## Packaging

Single pack height (mm):	90
Single pack width (mm):	158
Single pack weight (Kg):	0,701
Single pack depth (mm):	160
Single pack volume (dm3):	2,275