

### SIMPLEBUS DIGITAL MODULE. COLOUR: BLACK. IKALL SERIES

Complete with 128x64 dot graphic LCD display and 21-button keypad backlit with blue LEDs, stainless steel finish. Also functions as a coded electronic key module. It has an electronic directory module which can store up to 3800 user names and 6400 lock-release passwords. Names can be scrolled using the two search buttons or by entering the initial letter of the required name. Once the right name has been found, simply press the call button. The user code can also be entered directly to make the call. User programming is simple with the PC software art. 1249B, via the USB and RS485 ports. Compatible with all SBTOP functions and products. Allows call addressing for up to 120000 users. Allows customisation by means of an initial welcome message and offers dual language user interface operation. Can be used in conjunction with Simplekey electronic keys for automatic updating of names in the directory. Includes the CD-ROM with serial download SW art. 1249B for installation on a PC, in addition to the USB connection cable. Can be used to quickly program the directory of names in different calling modes, or to enter the lock-release password and initial welcome message. Allows archive management on PC. Dimensions: 112x180x40 mm.



#### Main specifications

Backlighting colour: **LED BLUE**

#### Software/firmware specifications

No. user codes: **3800**

No. of storable users: **3800**

#### Hardware specifications

Vandal Resistant IK: **No**

Total buttons: **18**

Sensitive Touch technology: **Yes**

#### Functions

Key button function: **Yes**

#### General info

Product height (mm): **180**

Product width (mm): **112**

Product depth (mm): **40**

Product colour: **BLACK RAL9005**

Operating temperature (°C): **-25/55**

Intrastat code: **8517709000**

#### Compatibility

Simplebus Top system: **Yes**

Simplebus Color system: **Yes**

Simplebus 2 system: **Yes**

# DATA SHEET

## Mounting/Installation

Flush-mounted:	Yes
Wall-mounted:	Yes

## Audio/video specifications

Display resolution (H x V):	128x64 DOTS
Audio system:	Yes
Audio/video system:	Yes
Type of display:	LCD

## Connectivity

Type of connections/ports:	RS485, USB
RS485 ports:	1

## Electrical specifications

Maximum current absorption (mA):	80
----------------------------------	----

## Packaging

Single pack height (mm):	160
Single pack width (mm):	160
Single pack weight (Kg):	0,7
Single pack depth (mm):	95
Single pack volume (dm3):	2,432