

TOUCH SCREEN STAINLESS STEEL A/V ENTRANCE PANEL
? VIP

Stainless steel flush-mounted 316 entrance panel with 7" capacitive touch screen with impact-proof glass. IK08 certified. Configurable graphics (list of names with search, up to 60 virtual buttons (or 10 with images, name directory, access codes up to 8 digits). Integrated RFID reader which can be used in conjunction with Simplekey. Users and settings are simple to program using VIP Manager part. 1449. It is compatible with all VIP products and functions. Pre-assembled with VIP a/v unit part. 4682C for audio/video/door lock management, and flush-mounted box with concealed fixing screws. Dimensions 342x182x3 mm.

**Main specifications**

Signal/noise ratio (dB): 48

Software/firmware specifications

Camera pixels (H x V): 500x582

Hardware specifications

Vandal Resistant IK: IK08

IP protection rating: IP54

DDE function: Yes

Functions

Key button function: Yes

Loudspeaker volume control: Yes

General info

Product height (mm): 342

Product width (mm): 182

Product depth (mm): 60

Operating temperature (°C): -25/50

Compatibility

Video door entry family: Yes

Vip system: Yes

Mounting/Installation

Flush-mounted: Yes

DATA SHEET

Audio/video specifications

Type of sensor:	1/4' CCD
Display size (inches):	8
Display resolution (H x V):	800x480 pixel
Audio system:	No
Audio/video system:	Yes
Type of display:	Touch screen

Connectivity

Type of connections/ports:	RS485, ETH
Ethernet ports:	1
RS485 ports:	2

Electrical specifications

Absorption:	25 W
-------------	------

Packaging

Single pack height (mm):	130
Single pack width (mm):	515
Single pack weight (Kg):	4,35
Single pack depth (mm):	235