

## SBC A/V UNIT W/ COLOR CAMERA FOR IKALL ENTRANCE PANEL

Simplebus Color system audio-video unit with terminal block complete with front-adjustable wide-angle 1/4" color camera and LED camera illumination. Complete with terminal block and digital audio management system with Eco-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and DIP SWITCH with 8 positions for programming calls to users. Audio-visual indications for disabled individuals assistance request can be activated via programming. 33Vdc power supply via special power supply unit Art. 1595. On-board electronic lockrelease function (3A), plus C, NC, NO 10A relay contacts. For use in modules Art. 33410, 33411 and 33412. Dimensions: 4"x2.2"x1.5". Compatible with all SBTOP functions and products. Allows call addressing for up to 120000 users. Timed lock-release input and door open indication.



### Main specifications

Signal/noise ratio (dB):	48
Video output:	1 Vpp / 75 PAL

### Software/firmware specifications

Camera pixels (H x V):	500x582
------------------------	---------

### Hardware specifications

DDE function:	Yes
---------------	-----

### Functions

Key button function:	Yes
Loudspeaker volume control:	Yes
Microphone volume control:	Yes

### General info

Product height (mm):	55
Product width (mm):	104
Product depth (mm):	35
Operating temperature (°C):	-25/55
EAN product code:	8023903209174
Intrastat code:	85176910
S/N ratio dB:	48

### Compatibility

Simplebus Top system:	Yes
Simplebus Color system:	Yes

# DATA SHEET

Simplebus 2 system:	Yes
---------------------	-----

## Audio/video specifications

Type of sensor:	1/4" CCD
-----------------	----------

Horizontal resolution (TVL):	420
------------------------------	-----

Audio system:	No
---------------	----

Audio/video system:	Yes
---------------------	-----

## Technical properties

Sensitivity (lux):	1
--------------------	---

Type of camera:	COLOR
-----------------	-------

## Electrical specifications

Maximum current absorption (mA):	400
----------------------------------	-----

## Packaging

Single pack height (mm):	53
--------------------------	----

Single pack width (mm):	110
-------------------------	-----

Single pack weight (Kg):	0,223
--------------------------	-------

Single pack depth (mm):	94
-------------------------	----

Single pack volume (dm3):	0,548
---------------------------	-------