


TOP JAMB (PUSH SIDE) MOUNTING



- Ideal for multi-door applications since cost per door leaf decrease significantly as the number of door leaves increases.
- Standard, plate mounted 4820 series closer shipped with regular arm, metal cover, and wood and machine screw pack. See 4820 Series page 19 for options.
- Meets ADA requirements (power mode).
- Non-sized cylinders for interior doors to 4'6" and exterior doors to 3'6".
- Non-handed.
- Requires additional system components. See CONTROL BOX pages 26-28 and ACTUATORS & ACCESSORIES, page 121.
- Standard or optional custom powder coated finish, end caps are black.
- Optional plated finish on cover, arm, and fasteners.

The 4820 AUTO EQUALIZER™ is LCN's pneumatically powered MULTI-DOOR solution. This low-energy automatic operator provides easy access for people with disabilities, the elderly, or the frail. Designed primarily for manual opening applications that occasionally require automatic opening.

- **Multi-Door Solution**
- **Utilizes a 10,000,000 Cycle Heavy Duty Door Closer**
- **Quiet, Efficient & Reliable**
- **Requires Control Boxes with integral compressor or control box using auxiliary air supply.**
- **No Guard Rails/Safety Mats Required**

The 4820 Series is UL and cUL228 and meets the provisions of ANSI Standards A117.1, A156.19, and the Americans with Disabilities Act.

MOUNTING	FINISH	COVER	CYLINDER	*ARM FUNCTION
TOP JAMB (PULL SIDE)	POWDER COAT	NON-HANDED	POWER OPERATOR	STANDARD (SINGLE)
TOP JAMB (PUSH SIDE)	PLATED	NON-SIZED	HOLD-OPEN	REGULAR (DOUBLE)
PARALLEL ARM	PLASTIC	ACCESSIBILITY*		EXTRA DUTY
CONCEALED	METAL			CUSH-N-STOP
				SPRING CUSH
				90°

● AVAILABLE

● Meets ADA requirements (power mode).

○ NOT AVAILABLE


* See individual series for maximum manual opening.

LCN 4820 SERIES

TOP JAMB (PUSH SIDE) MOUNTING

MAXIMUM OPENING

Templating allows 90° power opening and 100° manual opening.



- ▶ **Butt Hinges** should not exceed 5" (127 mm) in width.
- ▶ **Auxiliary Stop is recommended.**
- ▶ **Reveal** of 4 1/2" (114 mm) allows up to 90° power opening and 100° manual opening. 8" (203 mm) allows up to 90° power opening and 100° manual opening with LONG ARM where standard rod and shoe is replaced with optional LONG ROD AND SHOE, 4820-79LR.
- ▶ **Head Frame** minimum 1 3/4" (44 mm).
With flush ceiling use PLATE, 4820-18G substituted for standard plate.
- ▶ **Top Rail** minimum 1 3/4" (44 mm).
Closer on 4820-18G plate requires 3" (76 mm) minimum.
- ▶ **System Diagram** See "AUTOMATIC OPERATORS" section pages 7-8 for typical system wiring, and page 28 for electrical and pneumatic data for control boxes.

Options

- ▶ Long arm.
- ▶ 18G plate.

Special Templates

Customized installation templates or products may be available to solve unusual applications.

Contact LCN for assistance.


LCN 4820 SERIES

CYLINDERS

CYLINDER ONLY, 4822-3971

Standard, non-handed, cast iron cylinder.


3971



CYLINDER ASSEMBLY, 4822-3071

Standard, non-handed, cast iron cylinder. Includes; 4820-18 Mounting Plate or 4820-18G Mounting Plate (must specify).

3071




COVERS

COVER, 4820-72MC

Standard, non-handed metal cover with black end caps.

72MC




ARMS

REGULAR ARM, 4820-3077

Non-handed arm.

LONG ARM, 4820-3077L

Arm includes LONG ROD AND SHOE, 4820-79LR for deep reveals.




INSTALLATION ACCESSORIES

PLATE, 4820-18

Standard mounting plate.


Plate requires minimum 1 3/4" (44 mm) minimum head frame and 2" (51 mm) top rail.



PLATE, 4820-18G

Replaces standard plate for flush ceiling condition.

Plate requires minimum 1 3/4" (44 mm) minimum head frame and 3" (76 mm) top rail.



LCN 4820 SERIES

TABLE OF SIZES

Non-sized 4820 Series cylinder is adjustable from size 2 through size 5 and is shipped set to size 3. Closing power of 4820 Series closers may be increased 50%.

→ Indicates recommended range of door width for closer size.

EXTERIOR (and VESTIBULE) DOOR WIDTH

	24"	30"	36"	42"
	610mm	762mm	914mm	1067mm
4822	size 3	size 4	size 5	
Minimum Door Width				

INTERIOR DOOR WIDTH

	24"	34"	38"	48"	54"
	610mm	864mm	965mm	1219mm	1372mm
4822	size 2	size 3	size 4	size 5	
Minimum Door Width					

HOW-TO-ORDER 4820 SERIES CLOSERS

1. SPECIFY FINISH.

Standard Powder Coat _____
Aluminum, Dark Bronze, Brass.

Closer will be shipped with:

- STANDARD CYLINDER,
- STANDARD METAL COVER,
- REGULAR ARM,
- WOOD and MACHINE SCREW PACK,

unless options listed below are selected.

CLOSER OPTIONS

FINISH

Custom Powder Coat (RAL) _____
 Plated Finish, US _____

ARM

Long (LONG)

SCREW PACK

TB*, Wood & Machine Screw (TBWMS)

*Specify door thickness if other than 1 3/4".

INSTALLATION ACCESSORIES

Plate, 4820-18
 Plate, 4820-18G

SPECIAL TEMPLATE

ST-_____