# **DATA SHEET**

# COD. 5702

### BRAVO HANDSET VERSION COLOR MONITOR

Handset version BRAVO monitor with 4? color screen, the brilliant white gloss finish combined with the silver color base combined with the etched glass effect facia. It is fitted as standard with door open pushbuttons and two pushbuttons for various functions, signalling LED, brightness adjustment, contrast adjustment, and slide call volume adjustment. The ?Privacy? function, which allows the privacy to be temporarily excluded, is standard and is obtained by positioning the call volume on zero. It can be converted into a desk version with art. 5712. Dimensions: 8.3?x8.9?x2.2?



## **Hardware specifications**

Customisable housing:	Yes
Additional buttons:	4
Total buttons:	7
Sensitive Touch technology:	No

### **Functions**

Privacy function:	Yes
Display brightness control:	Yes
Switchboard call function:	Yes
Privacy conversation function:	Yes
Induction loop function:	No
Key button function:	Yes
Hands-free function:	No
Full Duplex hands-free function:	No
Display colour control:	Yes
Display contrast control:	No
Loudspeaker volume control:	No
Microphone volume control:	Yes
Ringtone volume control:	Yes

### **General info**

Product height (mm):	225
Product width (mm):	215
Product depth (mm):	55
Product colour:	WHITE RAL9003, TEMPLATE GREY
Operating temperature (°C):	-5/55



# **DATA SHEET**

Intrastat code: 85176910		EAN product code:	8023903155600	
Simplebus Top system: Yes		Intrastat code:	85176910	
Simplebus Top system: Yes	Com	natibility		
Simplebus Color system: Traditional system: Yes Semplified system: Yes Comelbus system: Yes Comtel system: Yes Comtel system: Yes Comtel system: Yes  Mounting/Installation Flush-mounted: No Wall-mounted: Yes Desk base-mounted: Yes Surface-mounted: Yes JIN modules (no.): 1  Audio/video specifications Display size (inches): ABW or colour display: OSD display: No Touch screen display: No Display resolution (H x V): Audio system: Audio/video system: Type of display: LCD  Electrical specifications Maximum current absorption (mA): Single pack width (mm): Single pack weight (Kg): Single pack weight (Kg): Single pack weight (Kg): Single pack weight (Kg): Single pack depth (mm):	00111		Vos	
Traditional system: Yes   Semplified system: Yes   Comelbus system: Yes   Comelbus system: Yes   Comtel system: Yes   Yes   Commended: Yes   Obek base-mounted:				
Semplified system: Yes				
Comelbus system: Yes				
No				
Flush-mounted: No   Wall-mounted: Yes   Desk base-mounted: Yes   Desk base-mounted: Yes   DIN modules (no.): 1   1				
Flush-mounted: No   Wall-mounted: Yes				
Wall-mounted: Yes Desk base-mounted: Yes Surface-mounted: Yes DIN modules (no.): 1  Audio/video specifications Display size (inches): 4 BW or colour display: COLOR OSD display: No Touch screen display: No Display resolution (H x V): 960x234 pixel Audio system: No Audio/video system: Yes Type of display: LCD  Electrical specifications Maximum current absorption (mA): 250  Packaging Single pack height (mm): 90 Single pack weight (Kg): 1,032 Single pack depth (mm): 248	wou	_	No	
Desk base-mounted: Yes Surface-mounted: Yes DIN modules (no.): 1  Audio/video specifications Display size (inches): 4 B/W or colour display: COLOR OSD display: No Touch screen display: No Display resolution (H x V): 960x234 pixel Audio system: No Audio/video system: Yes Type of display: LCD  Electrical specifications Maximum current absorption (mA): 250  Packaging Single pack height (mm): 90 Single pack weight (Kg): 1,032 Single pack depth (mm): 248				
Surface-mounted: Yes DIN modules (no.): 1  Audio/video specifications  Display size (inches): 4  B/W or colour display: COLOR OSD display: No Touch screen display: No Display resolution (H x V): 960x234 pixel Audio system: No Audio/video system: Yes Type of display: LCD  Electrical specifications Maximum current absorption (mA): 250  Packaging Single pack height (mm): 90 Single pack width (mm): 275 Single pack weight (Kg): 1,032 Single pack depth (mm): 248				
DIN modules (no.): 1				
Audio/video specifications  Display size (inches): 4  B/W or colour display: COLOR  OSD display: No  Touch screen display: No  Display resolution (H x V): 960x234 pixel  Audio system: No  Audio/video system: Yes  Type of display: LCD  Electrical specifications  Maximum current absorption (mA): 250  Packaging  Single pack height (mm): 90  Single pack width (mm): 275  Single pack weight (Kg): 1,032  Single pack depth (mm): 248				
OSD display:  Touch screen display:  No Display resolution (H x V): Audio system: No Audio/video system: Yes Type of display: LCD  Electrical specifications Maximum current absorption (mA): 250  Packaging Single pack height (mm): Single pack weight (Kg): Single pack depth (mm): 248	Auui	Display size (inches):		
OSD display:  Touch screen display:  No Display resolution (H x V): Audio system: No Audio/video system: Yes Type of display: LCD  Electrical specifications Maximum current absorption (mA): 250  Packaging Single pack height (mm): Single pack weight (Kg): Single pack depth (mm): 248				
Touch screen display:  Display resolution (H x V):  Audio system:  Audio/video system:  Type of display:  Electrical specifications  Maximum current absorption (mA):  Single pack height (mm):  Single pack weight (Kg):  Single pack depth (mm):			No	
Display resolution (H x V):  Audio system:  No Audio/video system:  Type of display:  Electrical specifications  Maximum current absorption (mA):  250  Packaging  Single pack height (mm):  Single pack width (mm):  Single pack weight (Kg):  Single pack depth (mm):  248			No	
Audio/video system: Audio/video system: Type of display:  Electrical specifications Maximum current absorption (mA):  Single pack height (mm): Single pack width (mm): Single pack weight (Kg): Single pack depth (mm): Single pack depth (mm): 275 Single pack depth (mm): 248			960x234 pixel	
Audio/video system: Yes Type of display: LCD  Electrical specifications  Maximum current absorption (mA): 250  Packaging Single pack height (mm): 90 Single pack width (mm): 275 Single pack weight (Kg): 1,032 Single pack depth (mm): 248				
Electrical specifications  Maximum current absorption (mA): 250  Packaging  Single pack height (mm): 90  Single pack width (mm): 275  Single pack weight (Kg): 1,032  Single pack depth (mm): 248		Audio/video system:	Yes	
Maximum current absorption (mA):  250  Packaging  Single pack height (mm):  Single pack width (mm):  275  Single pack weight (Kg):  1,032  Single pack depth (mm):  248		Type of display:	LCD	
Maximum current absorption (mA):  250  Packaging  Single pack height (mm):  Single pack width (mm):  275  Single pack weight (Kg):  1,032  Single pack depth (mm):  248	Elec	trical specifications		
Single pack height (mm):  Single pack width (mm):  275  Single pack weight (Kg):  1,032  Single pack depth (mm):  248			250	
Single pack height (mm):  Single pack width (mm):  275  Single pack weight (Kg):  1,032  Single pack depth (mm):  248	Pack	raning		
Single pack width (mm):  Single pack weight (Kg):  Single pack depth (mm):  275  248	. acr		90	
Single pack weight (Kg):1,032Single pack depth (mm):248				
Single pack depth (mm): 248				

