

# 5822T

## WIRELESS TILT SENSOR TRANSMITTER



Honeywell's 5822T Wireless Tilt Sensor Transmitter is designed to mount vertically on surfaces that tilt horizontally when opened — providing an easy way to secure garage doors or basement tilt windows. Any time the sensor detects tilt movement, a notification is transmitted to the control panel. The sensor can be programmed as a monitored or notification only zone. Includes cover tamper and battery supervision.

## FEATURES

- Easy to install – use double sided tape or screws (included). Screws must be used in installations where temperatures can drop to 32°F (0°C) or below.
- Internal LED for easy programming
- Reliable 5800 Series Wireless
- Case tamper and battery supervision

## SPECIFICATIONS

### Battery (included)\*:

1 x 3 V, Lithium

\*Panasonic CR123A, Duracell DL123, Duracell DL123A or Honeywell 466

### Operating Temperature:

0°F to +131°F (-17°C to +55°C)

### Relative Humidity:

95% max. (non-condensing)

### Dimensions:

1-9/16" W x 3-1/16" H x 1-3/16" D  
(40 mm x 78 mm x 30 mm)

### Compatibility:

- Honeywell 5800 Series Wireless
  - Loop 1 terminals
  - Loop 3 tilt sensor
- FCC part 15, Class B verified
- IC, ICES-003, Class B verified

## ORDERING

5822T

Wireless Tilt Sensor Transmitter

### For more information:

[www.honeywell.com/security](http://www.honeywell.com/security)

### Automation and Control Solutions

Honeywell Security Products Americas  
2 Corporate Center Dr. Suite 100  
P.O. Box 9040  
Melville, NY 11747  
1.800.467.5875  
[www.honeywell.com](http://www.honeywell.com)

# Honeywell

L/5822TD/D  
July 2013  
© 2013 Honeywell International Inc.