STI PROTECTIVE CABINETS



STI-7530 with Key Lock


PRODUCT OVERVIEW

Multipurpose lockable cabinets for remote annunciators, fire alarm control panels or other electronic products which require physical or environmental protection. Helps guard against vandalism (accidental or intentional), as well as dirt, dust and grime (models without alarm). Covers mount on the wall enabling the unit to be stored in a central location. The cabinets are available with a key or thumb lock, with or without siren alarm or siren/strobe alarm. They also have an additional eyelet for a secondary lock or safety seal.

HOW THEY WORK

Cabinets are constructed of a clear polycarbonate which allows the unit within to be highly visible and accessible. When cabinet with siren alarm is opened, the alarm emits an ear piercing siren (model with siren/strobe alarm also flashes), drawing immediate attention to the area. Operator has to unlock the unit and open the lid for access.





KEY FEATURES General Information

- Clear UV-stabilized polycarbonate cover.
- Three year guarantee against breakage of polycarbonate in normal use (one year on electro mechanical and electronic components).

Design

- · Steel internal mounting plate provided.
- · Design allows visibility at any angle.
- Additional eyelet can be used for secondary padlock or safety seal.

Construction

• Constructed of tough polycarbonate – the same material used in football helmets.

Installation

STI-7550

- External mounting tabs.
- · Complete with mounting hardware and gasket.
- Typical working properties of polycarbonate are -40° to 250°F (-40° to 121°C).
- Tamperproof mounting screws available.

Options

- · Includes thumb lock or key lock.
- Models available with or without siren alarm or siren/strobe alarm (see separate spec sheets for specific details. For siren alarm only, see STI- 6400. For siren/strobe alarm, see STI-SA5000).

STI-7520 Cabinet Series

- · Frosted polycarbonate back box.
- · Type 4X Approved, UL Listed.

STI-7530 Cabinet Series

- · Internal drill dimples.
- · Optional adjustable wire shelf available.

STI-7550 Cabinet Series

- · Two rotary action latches.
- · Optional wire shelf available.
- · Type 4X Approved, UL Listed.



STI Protective Cabinets

Dimensions and Technical Information

MODELS AVAILABLE

S / W/ (IE/ (DEE
Type 4X Cabinet with key lock - clear
Type 4X Cabinet with thumb lock - clear
Cabinet with key lock and siren alarm - clear
Cabinet with thumb lock and siren alarm - clear
Cabinet with key lock and siren/strobe alarm - clear
Cabinet with thumb lock and siren/strobe alarm - clear
Cabinet with key lock - clear
Cabinet with thumb lock - clear
Cabinet with key lock and siren alarm - clear
Cabinet with thumb lock and siren alarm - clear
Cabinet with key lock and siren/strobe alarm - clear
Cabinet with thumb lock and siren/strobe alarm - clear
Cabinet with key lock - clear
Cabinet with thumb lock - clear
Cabinet with key lock and siren alarm - clear
Cabinet with thumb lock and siren alarm - clear
Cabinet with key lock and siren/strobe alarm - clear

STI-7555 Cabinet with thumb lock and siren/strobe alarm - clear

Accessories

STI-6453	Replacement siren alarm
05000	Replacement siren/strobe alarm
07530WR	Wire shelf for STI-7530 series
07550WR	Wire shelf for STI-7550 series
18021	Type 4X 3/4" rigid conduit hub (not for use with
	STI-7530 series)
18054	Additional key #CH751
18075	Replacement key for siren/strobe alarm
19032	Replacement key #2341 for siren alarm
SUB-82	#8 x 1.5" snake eye tamper resistant stainless steel
	screw (qty. 4)
19038	Snake eye bit

APPROVALS & WARRANTY

TESTING

STI-7520 and STI-7521 have been tested and approved or listed by:

- · UL and cUL S7255
- Type 4X Certified
- Tested to UL38, UL50 and UL2017
 STI-7550 and STI-7551 have been tested and approved or listed by:
- · UL S7255
- Type 4X Certified


WARRANTY


Three year guarantee against breakage of polycarbonate in normal use (one year on electro mechanical and electronic components).


	Α	В	С	D	E
STI-7520/7521	0.075 1-	40.075 -	0.005 1-	10	N/A
STI-7522/7523	8.875 in. (225mm)	10.875 in. (276mm)	3.625 in. (92mm)	12 in. (305mm)	19 in. (483mm)
STI-7524/7525	(2231111)	(2701111)	(9211111)	(3031111)	19.46 in. (494.34mm)
STI-7530/7531	12.2 in.	14.2 in.	6.44 in.	16.5 in.	N/A
STI-7532/7533	(310mm)	(361mm)	(164mm)	(419mm)	23 in. (584mm)
STI-7534/7535	. ,			. ,	23.5 in. (597mm)
STI-7550-7551	19.75 in.	24.75 in.	7.31 in.	27.5 in.	N/A
STI-7552/7553	(502mm)	(629mm)	(186mm)	(699mm)	34.7 in. (881mm)
STI-7554/7555		(0201111)	(1001111)	(cooniny	35 in. (889mm)

*Additional eyelet:

STI-7520 and STI-7530 Series - 1/4" diameter STI-7550 Series - 5/8" diameter









Safety Technology International, Inc. 2306 Airport Road Waterford, Michigan 48327, USA Tel: 248-673-9898 Fax: 248-673-1246 Toll-free: 800-888-4784 info@sti-usa.com www.sti-usa.com Unit 49G Pipers Road Park Farm Industrial Estate Redditch, Worcestershire B98 OHU England Tel: 44 (0) 1527 520 999 Fax: 44 (0) 1527 501 999 www.sti-europe.com