

600-lb Electromagnetic Locks

E-941SA-600 E-941SA-600PO UL Listed With bond sensor, status LED, UL listed

Features:

- 600-lb Holding force
- Anodized aluminum housing (US 28)
- Selectable 12/24 VDC operation
- No residual magnetism
- MOV surge protection
- Adjustable mounting bracket
- Complete mounting hardware for typical installations
- "L" and "Z" brackets available for easy mounting
- Detachable faceplate

E-941SA-600PQ Only:

Specifications:

Model

Weight

Status LED

Holding force

Current draw

Operating voltage

Bond sensor relay

Operating temperature

 Built-in dual-colored status LED and bond sensor to indicate locking status

E-941SA-600

600-lb (272kg)

12/24 VDC ± 10% 500mA@12VDC

250mA@24VDC

14°~131° F (-10°~55° C)

4-lb, 6-oz (2kg)

E-941SA-600PQ

1

~

| | - |
|-------|----------------------------------|
| Green | Door is closed and locked |
| Red | Door is not closed and/or locked |
| Off | Door in use / No power |


Bond sensor relay rated 3A@12VDC

12VDC


24VDC



Dimensions:



Armature Plate



SECO-LARM[®] U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA, 92606 Tel (CA & Int'l): (949) 261-2999 | (800) 662-0800 Website: www.seco-larm.com | Email: sales@seco-larm.com

Copyright 2013 © SECO-LARM U.S A, Inc. All rights reserved. The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

PiE-941SA-600.docx



Access

US