





### Standard Features

- Completely surface mounted
- Stainless steel construction
- Tamper resistant
- Static strength 1,500 lbs.
- Dynamic strength 70 ft-lbs.
- Endurance 1,000,000 cycles
- Field selectable fail safe/fail secure
- Dual voltage 12 or 24VDC
- Horizontal adjustment
- Non-handed
- Internally mounted solenoid
- Accommodates up to 3/4" Pullman latch
- Five-year limited warranty

### Optional Features

- **LBM** » Latchbolt monitor
- **LBSM** » Latchbolt strike monitor

### Accessories

- 9400/9500/9600-108** » Spacer plate (black or 630 finish)
- SMB** » Surface mounting box
- 2001M** » Plug-in bridge rectifier
- 2004M** » ElectroLynx® adapter
- 2005M3** » SMART Pac® III
- 2006M** » Plug-in buzzer

### Finishes

- 630** » Satin stainless steel
- 605** » Bright brass
- 606** » Satin brass
- 612** » Satin bronze
- 613** » Bronze toned
- 629** » Bright stainless steel



RIM EXIT DEVICES

FIELD SELECTABLE  
(12 OR 24VDC)FIELD SELECTABLE  
(FAIL SECURE / FAIL SAFE)

GRADE 1



OUTDOOR RATED

UL 1034  
BURGLARY LISTEDANSI A250.13-2003  
WINDSTORM RESISTANT