



ALTV2416300UL

Overview

ALTV2416300UL provides 24VAC or 28VAC distributed via Sixteen (16) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications***Input:***

- 115VAC, 50/60Hz, 2.7 amp.

Output:

- Sixteen (16) fuse protected outputs.
- 24VAC @ 12.5 amp (300VA) supply current
(0.781 amp per device, 3.5 amp max.)
or 28VAC @ 10 amp (280VA) supply current
(0.625 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 153.55 BTU/Hr.
 - 28VAC: 143.31 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement: 310.5VA.

Features:

- Secondary fuse rated @ 10 amp/250V.
- AC power LED.
- Power ON/OFF switch.
- Spare fuses provided.
(all models w/primary and/or secondary fuses).

Mechanical:

- Enclosure Dimensions (H x W x D approx.):
13.5" (343mm) x 13" (330mm) x 3.25" (83mm)
- Product weight (approx.): 17.1 Lbs (7.756 kg)
- Shipping weight (approx.): 18.1 Lbs (8.21 kg)

Agency Approvals

UL Listed for Commercial CCTV Equipment
(UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98,
Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions

13.5" (343mm) x 13" (330mm) x 3.25" (83mm)

