



ALTV2416350

Overview

ALTV2416350 AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via Sixteen (16) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- 115VAC, 50/60Hz, 2.7 amp.

Output:

- Sixteen (16) fuse protected outputs.
- 24VAC @ 14 amp (350VA) supply current
(0.875 amp per device, 3.5 amp max.)
- or 28VAC @ 12.5 amp (350VA) supply current
(0.781 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 171.97 BTU/Hr.
 - 28VAC: 179.14 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement: 310.5VA.

Features:

- Main fuse rated @ 15 amp/32V.
- AC power LED.
- Spare fuses provided.
(all models w/primary and/or secondary fuses).

Mechanical:

- Enclosure Dimensions (H x W x D approx.):
13.5" (343mm) x 13" (330mm) x 3.25" (83mm).
- Product weight (approx.): 17.2 Lbs (7.81 kg).
- Shipping weight (approx.): 18.2 Lbs (8.26 kg).

Agency Approvals



European Conformity

Enclosure Dimensions

13.5" (343mm) x 13" (330mm) x 3.25" (83mm)

