



ALTV2416350CB

**Overview**

ALTV2416350CB AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via Sixteen (16) PTC protected outputs for powering CCTV Cameras, heaters and other video accessories.

**Specifications*****Input:***

- 115VAC, 50/60Hz, 2.7 amp.

***Output:***

- Sixteen (16) PTC protected outputs.
- 24VAC @ 14 amp (350VA) supply current  
(0.875 amp per device, 2.5 amp max.)
- or 28VAC @ 12.5 amp (350VA) supply current  
(0.781 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
  - 24VAC: 171.97 BTU/Hr.
  - 28VAC: 179.14 BTU/Hr.

***Electrical (cont'd):***

- System AC input VA requirement: 310.5VA.

***Features:***

- Main fuse rated @ 15 amp/32V.
- AC power LED.

***Mechanical:***

- Enclosure Dimensions (H x W x D approx.):  
13.5" (343mm) x 13" (330mm) x 3.25" (83mm)
- Product weight (approx.): 17.2 Lbs (7.80 kg).
- Shipping weight (approx.): 18.2 Lbs (8.26 kg).

**Agency Approvals**

European Conformity

# **Enclosure Dimensions**

**13.5" (343mm) x 13" (330mm) x 3.25" (83mm)**

