



ALTV2416600UL

**Overview**

ALTV2416600UL provides 24VAC or 28VAC distributed via Sixteen (16) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

**Specifications****Input:**

- 115VAC, 50/60Hz, 5.4 amp.

**Output:**

- Sixteen (16) fuse protected outputs.
- 24VAC @ 25 amp (600VA) supply current  
(1.56 amp per device, 3.5 amp max.)  
or 28VAC @ 20 amp (560VA) supply current  
(1.25 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

**Electrical:**

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
  - 24VAC: 307.09 BTU/Hr.
  - 28VAC: 286.62 BTU/Hr.

**Electrical (cont'd):**

- System AC input VA requirement: 621VA.

**Features:**

- Secondary fuse rated @ 15 amp/250V.
- AC power LED.
- Power ON/OFF switch.
- Spare fuses provided.  
(all models w/primary and/or secondary fuses).

**Mechanical:**

- Enclosure Dimensions (H x W x D approx.):  
13.5" (343mm) x 13" (330mm) x 3.25" (83mm)
- Product weight (approx.): 22.7 Lbs (10.296 kg)
- Shipping weight (approx.): 23.7 Lbs (10.75 kg)

**Agency Approvals**

UL Listed for Commercial CCTV Equipment  
(UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98,  
Audio, Video and Similar Equipment.



European Conformity

**Enclosure Dimensions**  
13.5" (343mm) x 13" (330mm) x 3.25" (83mm)

