



ALTV248UL3

Overview

ALTV248UL3 provides 24VAC or 28VAC distributed via Eight (8) fuse protected power limited outputs for powering CCTV Cameras, heaters and other video accessories. Factory installed 3-wire line cord.

Specifications**Input:**

- 115VAC, 50/60Hz, 0.9 amp.

Output:

- Eight (8) fuse protected outputs.
- 24VAC @ 3.5 amp (85VA) supply current
(0.438 amp per device, 3.5 amp max.)
or 28VAC @ 3 amp (85VA) supply current
(0.375 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.: 42.99 BTU/Hr.
- System AC input VA requirement: 103.5VA.

Features:

- Secondary fuse rated @ 5 amp/250V.
- AC power LED.
- Power ON/OFF switch.
- Factory installed 3-wire line cord.
- Spare fuses provided.
(all models w/primary and/or secondary fuses).

Mechanical:

- Enclosure Dimensions (H x W x D approx.):
8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm)
- Product weight (approx.): 6 Lbs (2.721 kg).
- Shipping weight (approx.): 7 lbs. (3.175 kg).

Agency Approvals

UL Listed for Commercial CCTV Equipment
(UL 2044).



European Conformity



CUL Listed - CSA Standard C22.2 No.1-98,
Audio, Video and Similar Equipment.

Enclosure Dimensions

8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm)

