



### **Overview**

ALTV615DC416UL provide 6VDC to 15VDC distributed via sixteen (16) Class 2 Rated fuse protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

### **Specifications**

#### ***Input:***

- Input 115VAC, 50/60 Hz, 0.9 amp.

#### ***Output:***

- Sixteen (16) Class 2 Rated fuse protected power limited outputs.
- 6VDC to 15VDC field adjustable.
- 4 amp total continuous supply current (*0.25 amp per device, 3.5 amp max.*).
- Output fuses are rated @ 3.5 amp/250VAC.
- Filtered and electronically regulated outputs.

#### ***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- 9-23 BTU/Hr.
- System AC input VA requirement: 103.5VA.

#### ***Features:***

- AC input and DC output LED indicators.
- Illuminated power disconnect circuit breaker with manual reset.
- Spare fuse(s) provided.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

#### ***Mechanical:***

- NEMA1 enclosure.
- Enclosure Dimensions (H x W x D approx.): 13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)
- Product weight (approx.): 10.5 lbs. (4.76 kg.).
- Shipping weight (approx.): 11.0 lbs. (4.99 kg.).

### **Agency Approvals**



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

**Enclosure Dimensions (H x W x D) (approximate):**

13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)

