



ALTV615DC616UL3

Overview

ALTV615DC616UL3 provide 6VDC to 15VDC distributed via sixteen (16) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories. Factory installed 3-wire line cord.

Specifications**Input:**

- Input 115VAC, 50/60 Hz, 0.9 amp.

Output:

- Sixteen (16) fuse protected outputs.
- 6VDC to 15VDC field adjustable.
- 6 amp total continuous supply current
(0.375 amp per device, 3.5 amp max.).
- Output fuses are rated @ 3.5 amp/250VAC.
- Filtered and electronically regulated outputs.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 18.43-46.06 BTU/Hr.
- System AC input VA requirement: 103.5VA.

Features:

- AC input and DC output LED indicators.
- Factory installed 3-wire line cord.
- Illuminated power disconnect circuit breaker with manual reset.
- Spare fuse(s) provided.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

Mechanical:

- NEMA1 enclosure.
- Enclosure Dimensions (H x W x D approx.):
13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)
- Product weight (approx.): 14.3 lbs. (6.49 kg.).
- Shipping weight (approx.): 14.8 lbs. (6.71 kg.).

Agency Approvals

UL Listed for Commercial CCTV Equipment
(UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98,
Audio, Video and Similar Equipment.

Enclosure Dimensions (H x W x D) (approximate):

13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)

