



ALTV615DC8UL3

Overview

ALTV615DC8UL3 is designed with eight (8) individually Class 2 Rated fuse protected power limited outputs for powering CCTV Cameras and other video accessories. Factory installed 3-wire line cord.

Specifications

Input:

- Input 115VAC, 50/60 Hz, 0.9 amp.

Output:

- Eight (8) Class 2 Rated fuse protected power limited outputs.
- 6VDC to 15VDC field adjustable.
- 4 amp total continuous supply current (0.50 amp per device, 3.5 amp max.).
- Output fuses are rated @ 3.5 amp/250VAC.
- Filtered and electronically regulated outputs.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 12.28-30.71 BTU/Hr.
- System AC input VA requirement: 103.5VA.

Features:

- AC input and DC output LED indicators.
- Factory installed 3-wire line cord.
- Power ON/OFF switch.
- Spare fuse(s) provided.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

Mechanical:

- NEMA1 enclosure.
- Enclosure Dimensions (H x W x D approx.): 13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)
- Product weight (approx.): 11.5 lbs. (5.22 kg.).
- Shipping weight (approx.): 12.0 lbs. (5.44 kg.).

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



cUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

Enclosure Dimensions (H x W x D) (approximate):

13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)

