



PD4ULCB

### **Overview**

PD4ULCB Sub-Assembly power distribution module converts a single DC or AC input into four (4) individually PTC protected Class 2 Rated power-limited outputs.

### **Specifications**

#### **Input:**

- 12VDC or 24VDC up to 10 amp (total output current should not exceed max current rating of power supply employed).

#### **Output:**

- Four (4) PTC protected Class 2 Rated power-limited outputs.
- PTCs rated @ 2 amp/250V.
- Surge suppression.

#### **Electrical:**

- Operating temperature: 0° C to 49° C ambient.
- 61.42 or 122.84 BTU/Hr.

#### **Features:**

- Power LED indicator.

#### **Mechanical:**

- Product weight (approx.): 0.15 lbs. (0.07 kg).
- Shipping weight (approx.): 0.25 lbs. (0.11kg).

### **Agency Approvals**

**SECURITY  
SIGNALING**


UL Listed Sub-Assembly for Access Control System Units (UL 294) and for Power Supplies for Fire Protective Signaling Systems (UL 1481).



cUL Listed: General Signaling Equipment evaluated to CSA Standard C22.2 No.205-M1983.

### **Board Dimensions (W x L x H approximate)**

3.25" x 5.25" x 1" (82.55mm x 133.35mm x 25.4mm)

### **Mounting Diagram**

