

| PD4ULCB - UL Listed Sub-Assembly | Power Distribution Module

Overview:

The PD4ULCB is a UL Listed Sub-Assembly power distribution module, designed to convert a single DC input into four (4) PTC protected Class 2 Rated power-limited outputs.

Specifications:

Agency Listings:

 UL Listed Sub-Assembly for Access Control System Units (UL 294) and for Power Supplies for Fire Protective Signaling Systems (UL 1481).



SECURITY

• cUL Listed: General Signaling Equipment Evaluated to CSA Standard C22.2 No.205-M1983

Input:

• 12VDC or 24VDC up to 10 amp.

Outputs:

• Four (4) individually PTC protected outputs @ 2 amp per output max. current (total output current should not exceed max. current rating of power supply employed).

PTC Ratings:

• PTCs are rated @ 2A/250V.

Visual Indicators:

• Power on green LED indicator.

Board Dimensions (W x L x H approximate):

3.25" x 5.25" x 1" (82.55mm x 133.35mm x 25.4mm).

Installation Instructions:

Wiring methods shall be in accordance with the National Electrical Code/NFPA 70/NFPA 72/ANSI, and with all local codes and authorities having jurisdiction. Product is intended for indoor use only and should be installed by qualified personnel.

- 1. Refer to Sub Assembly Installation Instruction for mounting Rev. MS042511.
- 2. Connect the desired power supply output to the terminals marked [INPUT] (*Fig. 1*). **Note:** Left terminal is NEG. (-) and right terminal is POS. (+) (*Fig. 1*).
- 3. Measure output voltage before connecting devices. This helps avoiding potential damage.
- 4. Connect devices to be powered to the terminal pairs 1 to 4, marked [1P 1N] through [4P 4N]. All terminals with common suffix P "1P, 2P..." are same polarity.

Note: This product is a UL Listed Sub-Assembly for use with Altronix UL Listed power supplies as indicated in the installation manuals for the power supply.

Note: DC outputs are power-limited.

Caution: Do not expose to rain or moisture.

(#P) Positive DC outputs

(#N) Negative DC outputs



