



PD8ULCB

### **Overview**

PD8ULCB power distribution module converts a single AC or DC input into eight (8) individual PTC protected outputs.

### **Specifications**

#### **Input:**

- 12 or 24VDC up to 10 amp.  
(total output current should not exceed max current rating of power supply employed).

#### **Outputs:**

- Eight (8) individually fused outputs.
- PTCs rated @ 2.5 amp/250V
- Surge suppression.

#### **LED Indicators:**

- Power LED indicator.

#### **Electrical:**

- Operating temperature: – 25° C to 55° C ambient.

#### **Mechanical:**

- Snap track mountable (order part # ST3).
- Product weight (approx.): 0.25 lbs. (0.11 kg).
- Shipping weight (approx.): 0.30 lbs. (0.14kg).

### **Agency Approvals**

**SECURITY  
SIGNALLING**

**LISTED**

UL Listed Sub-Assembly for Access Control System Units (UL 294) and for Power Supplies for Fire Protective Signaling Systems (UL 1481).



cUL Listed: General Signaling Equipment evaluated to CSA Standard C22.2 No.205-M1983.

### **Board Dimensions (W x L x H approximate)**

3.25" x 5.25" x 1" (82.55mm x 133.35mm x 25.4mm)

### **Mounting Diagram**

