



# R2416300220 Rack Mount CCTV Power Supply

Rev. R2416300220\_10252012



R2416300220

## Overview

R2416300220 provides 24VAC or 28VAC distributed via sixteen (16) fuse protected outputs for powering CCTV cameras, heaters and other video accessories.

## Specifications

### **Input:**

- 220VAC, 50/60Hz, 1.5 amp.

### **Output:**

- Sixteen (16) fuse protected outputs.
- 24VAC @ 12.5 amp (300VA) supply current (0.78125 amp per device, 3.5 amp max.)
- or 28VAC @ 10 amp (300VA) supply current (0.625 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

### **Electrical:**

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
  - 24VAC: 153.55 BTU/Hr.
  - 28VAC: 143.31 BTU/Hr.
- System AC input VA requirement: 330VA.

### **Features:**

- Sixteen (16) power LEDs.
- Illuminated master power disconnect circuit breaker with manual reset.
- 3-wire grounded line cord.
- Removable terminal blocks with locking screw flange.
- Spare fuses provided.

### **Mechanical:**

- 2U rack mount chassis for use in standard EIA 19" rack.
- Enclosure Dimensions (H x W x D approx.): 3.26" x 19.125" x 8.5" (83mm x 486mm x 216mm)
- Product weight (approx.): 17.2 lbs. (10.43 kg).
- Shipping weight (approx.): 18.2 lbs. (10.89 kg).

## Agency Approvals



European Conformity

**Enclosure Dimensions (H x W x D approximate):**  
 3.26" x 19.125" x 8.5" (83mm x 486mm x 216mm)

