



R2416ULCBi **Isolated Rack Mount CCTV Power Supply**

Rev. DSR2416ULCBi_10252012



R2416ULCBi

Overview

R2416ULCBi provides 24VAC distributed via sixteen (16) isolated PTC protected Class 2 Rated power limited outputs for powering CCTV cameras, heaters and other video accessories.

Specifications

Input:

- 115VAC, 50/60Hz, 5.4 amp.

Output:

- Sixteen (16) isolated PTC protected Class 2 Rated power limited outputs.
- 24VAC @ 25 amp (600VA) supply current (1.6 amp per device, 2.5 amp max.)
- Outputs are rated @ 2.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 227 BTU/Hr.
- System AC input VA requirement: 690VA.

Features:

- Sixteen (16) power LEDs.
- Illuminated master power disconnect circuit breaker with manual reset.
- 3-wire grounded line cord.
- Removable terminal blocks with locking screw flange.

Mechanical:

- 2U rack mount chassis for use in standard EIA 19" rack.
- Enclosure Dimensions (H x W x D approx.): 3.26" (83mm) x 19.125" (486mm) x 8.5" (216mm)
- Product weight (approx.): 24.4 lbs. (11.07 kg).
- Shipping weight (approx.): 25.4 lbs. (11.52 kg).

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions (H x W x D) (approximate):
3.26" (83mm) x 19.125" (486mm) x 8.5" (216mm)

