



ALTV244CB

Overview

ALTV244CB AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via four (4) PTC protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications***Input:***

- 115VAC, 50/60Hz, 0.9 amp.

Output:

- Four (4) PTC protected outputs.
- 24VAC @ 4 amp (100VA) supply current
(1 amp per device, 2.5 amp max.)
- or 28VAC @ 3.5 amp (100VA) supply current
(0.875 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 49.13 BTU/Hr.
 - 28VAC: 50.16 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement: 103.5VA.

Features:

- Secondary fuse rated @ 5 amp/250V.
- AC power LED.
- Power ON/OFF switch.

Mechanical:

- Enclosure Dimensions (H x W x D approx.):
8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm)
- Product weight (approx.): 6.2 lbs. (2.812 kg).
- Shipping weight (approx.): 6.8 lbs. (3.084 kg).

Agency Approvals

European Conformity

Enclosure Dimensions

8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm)

