



Overview

ALTV248600UL provides 24VAC or 28VAC distributed via Eight (8) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- 115VAC, 50/60Hz, 5.4 amp.

Output:

- Eight (8) fuse protected outputs.
- 24VAC @ 25 amp (600VA) supply current
(3.125 amp per device, 3.5 amp max.)
- or 28VAC @ 20 amp (560VA) supply current
(2.5 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 307.09 BTU/Hr.
 - 28VAC: 286.62 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement: 621VA.

Features:

- Secondary fuse rated @ 15 amp/32V.
- AC power LED.
- Power ON/OFF switch.
- Spare fuses provided.
(all models w/primary and/or secondary fuses).

Mechanical:

- Enclosure Dimensions (H x W x D approx.):
13.5" x 13" x 3.25" (343mm x 330mm x 83mm)
- Product weight (approx.): 22.2 lbs (10.1 kg).
- Shipping weight (approx.): 23.2 lbs (10.5 kg).

Agency Approvals



UL Listed for Commercial CCTV Equipment
(UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98,
Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions (H x W x D approximate):
 13.5" x 13" x 3.25" (343mm x 330mm x 83mm)

