



**PRODUCT FEATURES**

- Allows powering of non-PoE devices from a PoE source
- 12 VDC output power derived from PoE source
- Selectable for 13W or 25W output
- Visual diagnostics by on-board LED
- MagnaCare® lifetime replacement, no fault warranty

**SPECIFICATIONS**

- UL 294B Listed
- UL/CUL 60950-1
- 30W IEEE 802.3at
- CSA C22.2 No.205-M1983, Signal Equipment
- RoHS Compliant

**Electrical:**

42.5 to 57VDC PoE Input

0.6 A input current

12 VDC output, 13 or 25W

10/100/1000 data rate  
Base-T compliant

**Operating Temperature:**

+32 to +120F [0 to + 49C]

# AQE SINGLE PORT EXTRACTOR

## Power over Ethernet

### Gigabit Data and Power All-in-One

The Securiton AQE30E is a single port Power over Ethernet (PoE) MidSpan Extractor designed for access control and security applications. This module provides 12 VDC up to a maximum of 25W output power to a non-PoE device from a PoE source. The AQE30E Extractor is used to power DC IP and PTZ cameras, access control, door controllers and other similar equipment.

The AQE Series Extractor provides RJ45 connectors for data input and output and two terminal strips for the DC output and power level selection.

Product Number	Input Amps	Output Voltage	Output Power	Data Rate – BASE-T Compliant	UL294B	UL/CUL 60950-1	IEEE 802.3at
AQE30E	0.6	12 VDC	1A/2A (13/25W)	10/100/1000	L	L	L

*L: Listed*

