



AQU126-8F8R Power Supply

The AQU126-8F8R power supply with battery charger/backup and supervision is a single voltage power supply that uses any AC power source from 90-240VAC/ 47-63Hz to provide up to 6 Amps @ 12VDC continuous output.

FEATURES:

- Clean, steady, accurate power output for best performance of access control equipment
- Compact modules for smaller footprint
- Universal transformer compatible with most international power
- Works in AC brownout down to 60 VAC
- Faster battery recharging under full load
- Automatic low-battery disconnect prevents deep discharge, maintains battery life
- Self-resetting circuit breakers for common conditions including:
 - Overcurrent
 - Thermal runaway
 - Reverse battery hookup
- Fuse protected against surge for AC input and DC output
- Class 2 power limited output
- Eight (8) channel power distribution with Access Control
 - Fire transfer relays with individual inputs and status LEDs
 - Each relay input activated from Low Current Open Collector, Normally Closed or Normally Open switch
 - Channels individually configured to FT Enabled/Disabled
 - Power limited fuse protected outputs, each with a green status LED indicator
 - Main power green/red LED indicates AC, DC or Reversed DC input
 - Pluggable terminal blocks by channel and function
- SPDT Form C outputs for remote monitoring of:
 - AC failure
 - Low battery
- Made in USA
- MagnaCare Lifetime Replacement No Fault Warranty
- UL Listed

SPECIFICATIONS: AQU126-8F8R

Power Module: AQU126

Electrical

Input Voltage Operating Range

90-240VAC
47-63Hz

Maximum Output Voltage

78 VA
6.5 Amps @ 12VDC

Continuous Output Voltage

72 VA
6 Amps @ 12VDC

Voltage Range

9.9 – 13.6VDC/ 13.65 typical

Operating Frequency

27KHz

Onboard Power Output

One (1) Output

Fuse Protection

Battery: 6 Amp
Current Overload: Fuse, self-resetting
Thermal Runaway: Fuse, self-resetting

Supervision/Monitoring

AC ON LED indicator: 6mA
DC ON LED indicator: 6mA
AC Fail notification: SPDT Form C 2 Amp
Low Battery: SPDT Form C 3 Amp

Regulatory

UL 294

RoHS lead free

Access Control: -8F8R

Electrical

Max board power use: 208mA

Fuses

Size: 050 Standard 3AGC
Output: 2A

Relays

Input Relays: 20ma required for activation
Output Relays: contacts rated 7A 125VAC max

Triggers

EOL: +/-60% of 2.2K ohms

Mechanical

Environment

Operating Temperature: -4 to +104°F
[-20 to +40°C]
Humidity: 95% RH non condensing

Dimensions

Enclosure: 14"x 9" x 3.5"

Power Board: 6.4" x 3.95" x 2.35"

Mounting: 5.36" x 3.54"

Access Control Module: 4.82" x 3.84" x 1.4"

Mounting: 3.41" x 4.50"

Shipping Weight: 7.65 lbs

*Use gauge appropriate for output voltage and wiring distance.

