



AQU126 Power Supply

The AQU126 power supply with battery charger/backup and supervision is a single voltage power supply that uses any AC power source from 90-240VAC/47-63Hz to provide up to 6 Amps @ 12VDC continuous output.

FEATURES:

- Clean, steady, accurate power output for best performance of access control equipment
- Compact modules for smaller footprint
- Universal transformer compatible with most international power
- Works in AC brownout down to 60 VAC
- Faster battery recharging under full load
- Automatic low-battery disconnect prevents deep discharge, maintains battery life
- Self-resetting circuit breakers for common conditions including:
 - Overcurrent
 - Thermal runaway
 - Reverse battery hookup
- Fuse protected against surge for AC input and DC output
- SPDT Form C outputs for remote monitoring of:
 - AC failure
 - Low battery
- Made in USA
- MagnaCare Lifetime Replacement No Fault Warranty
- UL and ULC Listed

SPECIFICATIONS: AQU126

Electrical

Input Voltage Operating Range

90-240VAC
47-63Hz

Maximum Output Voltage

78 VA
6.5 Amps @ 12VDC

Continuous Output Voltage

72 VA
6 Amps @ 12VDC

Voltage Range

9.8 – 13.67VDC/ 13.65 typical

Operating Frequency

27KHz

Onboard Power Output

One (1) Output

Fuse Protection

Battery: PTC 6 Amp
Current Overload: PTC, self-resetting
Thermal Runaway: PTC, self-resetting

Supervision/Monitoring

AC ON LED indicator: 6mA
DC ON LED indicator: 6mA
AC Fail notification: SPDT Form C 2 Amp
Low Battery: SPDT Form C 3 Amp

Environment

Operating Temperature: -4 to +104°F
[-20 to +40°C]

Humidity: 95% RH non condensing

Mechanical

Dimensions

Enclosure: 14"x 9" x 3.5"

Power Module: 6.4" x 3.95" x 2.35"

Mounting: 5.36" x 3.54"

Shipping Weight: 7.65 lbs

Regulatory

UL 294
UL 603
ULC-S318-96
UL 1481
ULC 527
CSA-C22.2 #205

RoHS lead free

