

## Series ASR Audible and Audible Strobe



### Description:

The Series ASR Audible and Audible Strobe products provide a range of warning alarms and strobes designed to cope with harsh environments providing weatherproof protection. Design features are incorporated to ensure safer and easier installation, while providing flexibility with fewer product variants.

Current: ASR-DC 450MA/MAX  
ASR-AC 115VAC - 130 MA  
230VAC - 65 MA  
ASRS-DC Max 700 MA

Nominal Voltage: 18 - 30VDC, 115/230VAC

Current Consumption  
(tone dependant): Between

Sound Output  
(tone dependant): Between 105 - 102dB

Alarm Tones: 42

IP Rating: IP66

Lens Colour: Red

Flash Rate: 1 Hz (60 per min)

Color: Gray

Strobe Type: U-Tube

Operating Temperature: -25°C to 70°C

Monitoring Mode: Polarizing Diode (DC models only)

Volume Control: 0 to -10dB



WE ENCOURAGE AND SUPPORT NICET CERTIFICATION  
3 YEAR WARRANTY  
ASR 08/14

### Features:

Up to 120dB(A) Output  
Three stage alarm (2 programmable - 1 standard)  
More light where required with asymmetric lens  
Easy access for installation with shallow base format  
42 Tones  
Weatherproof - Indoor/Outdoor

### Specification and Ordering Information:

Model Number	Order Code	Description
ASR-DC	4072	Audible only, 24VDC
ASR-AC	4073	Audible only, 115/230VAC
ASRS-R-DC	4075	Audible Strobe, 24VDC, Red lens



**NJ Location**  
273 Branchport Ave.  
Long Branch, NJ 07740  
P: 800-631-2148  
F: 732-222-8707  
www.coopernotification.com

**FL Location**  
7565 Commerce Ct.  
Sarasota, FL 34243  
P: 941-487-2300  
F: 941-487-2389

**VA Location**  
P: 877-459-7726  
F: 703-294-6560