TAKEX


Recording & Playback

VOICE SPEAKER CE **C** N1702 AV-100E (Power:12VDC)




- AV-100E is designed to give an audio message after being triggered by a PIR etc.
- Max. recording time is 8 secs. The message is easily recorded by just speaking into the built-in microphone.
- The message can be constructed to suit all applications.
- The message can be recorded over and over again.
- External relay input is Normally Open (Form A).
- Rain proof for outdoor installation.

WIRING



EXTERNAL DIMENSIONS (unit : mm)



Please Note : This sensor is designed to detect intrusion and to initiate an alarm; it is not a burglary or a crime preventing device. TAKEX is not responsible for damage, injury or losses caused by accident, theft, Acts of God (including inductive surge by lighting), abuse, misuse, abnormal usage, faulty installation or improper maintenance.



In Australia Takex America Inc. Unit 16/35 Garden Road, Clayton 3168 Victoria Australia Tel : 03-9546-0533 Fax: 03-9547-9450

Takex America Inc. Brisbane office : 1/50 Logan Road,Woolloongabba Queensland 4102, Australia Tel: 07-3891-3344 Fax: 07-3891-3355

In the U.K.

Takex Europe Ltd. Takex House, Aviary Court, Wade Road, Basingstoke, Hampshire, RG24 8PE, U.K. : (+44)01256-475555 Tel Fax: (+44)01256-466268 http://www.takexeurope.com

■SPECIFICATIONS

In Japan

83-1, Gojo-sotokan,

Higashino, Yamashina-ku,

http://www.takex-eng.co.jp/

Kyoto 607-8156, Japan

Tel: 81-75-501-6651

Fax: 81-75-593-3816

Takenaka Engineering Co., Ltd.

Model No.	AV-100E
Power supply	DC12V (non-polarity)
Power consumption	Stand by : 20mA or less, initiated : 500mA or less
Alarm input	Dry contact N/O, contact capacity 10mA or more
Synthesis method	ADM method
Recording method	Internal condenser microphone
Record/play back time	8 sec. (memory capacity : 256Kbit S-RAM)
Recorded memory back-up time	20 days or more, under no power supply (Temp. 25°C, battery charge time 30 minutes or more)
Sound output operation	One-shot playback (8 sec.) by receiving an alarm input signal (No retrigger action during play back)
Sound output	Max. 2W, 100dB or more : subject to good recording level
Sound volume control	Variable from zero to max.
Indication LED	(when recording) Recording level is indicated as follows : good : flashing, too low : Lights on, too loud : off
	(when playback) Light on during playback time (8 sec.)
Ambient temp. range	-20° C to $+50^{\circ}$ C, without condensation and freeze
Installation place	Indoor/outdoor (rain proof)
Weight	1,050g including wire 100g
Appearance	Black (Body : PC resin)

In the U.S.

Sunnyvale

Takex America Inc.

CA 94086, U.S.A.

Tel: 408-747-0100

Fax: 408-734-1100

http://www.takex.com

230E, Caribbean Drive

LEAF 0606E10-04