

Features

- Modular design
- Protected markings
- Multiple use
- Up to 4 digits per lamp
- Vertical or horizontal mounting

Description

The CM800-series Announciators are modular panels, permitting use in systems requiring from 16 to 344 annunciator lamps. The CM800 is suitable for use in emergency call, security alarm, services monitoring, and similar applications where visual and audible annunciation is required. (If audible indication is not needed, specify when ordering.) Identification markings are easily applied by dry transfer letter method or label maker.



**CM800/20 Announcer
with AM800/36 Add-on Panel and OF202 Frame**

Specifications

Power Required: 16 to 24 VAC or VDC

Connections: Screw terminals

Housings: Flush mounting, OH200
Surface mounting, OH300

Lamps available only in multiples of four.

Required Components

CM800-series Speaker Panel

AM800-series Add-On Panel

PK2019A Power & Control Unit

SS106 Transformer

Housing and Frame Chart for CM800

Number of Lamps	Flush	Width Cut-Out	Surface	Width Overall	Frame	Width Overall	Desk	Width
4 - 20	OH201	4-1/2"	OH301	6-1/8"	OF201	6-1/4"	IH302	9-1/2"
24 - 56	OH202	8-1/2"	OH302	10-1/8"	OF202	10-1/4"	IH302	9-1/2"
60 - 92	OH203	12-1/2"	OH303	14-1/8"	OF203	14-1/4"	IH303	13-1/2"
96 - 128	OH204	16-1/2"	OH304	18-1/8"	OF204	18-1/4"	IH304	17-1/2"
132 - 164	OH205	20-1/2"	OH305	22-1/8"	OF205	22-1/4"	IH305	21-1/2"
168 - 200	OH206	24-1/2"	OH306	26-1/8"	OF206	26-1/4"	IH306	25-1/2"

IH300 Series desk cabinets height: 6" depth: 17"
 OH200 Series wall cut-out height: 16-1/4" depth: 3-7/8"
 OH300 Series overall height: 17-3/4" depth: 3-5/8"
 OF200 Series overall height: 17-3/4" depth: 2-1/2"