

# **United Security** Products, Inc.

# CVD-2020

Full Featured Security System with 4 Independent Voice Channels

and Universal Cellular Dialer Backup with Cell Phone/SIM Card

Onsite or at Remote Locations, USP's Cellular Auto Voice Dialer Security Systems offer Reliable Low Cost Monitoring Solutions. No phone line, No contract, and No monitoring fees required. Secures RVs, Cabins, Boats, Storage Garages, Containers, Shops, Manufacturing Plants, etc. Monitors Signal Change in Operating Status of Remote Equipment or Machinery. Backs Up primary alarm system if phone lines are cut

# 3000000000000

CVD-2020 is a completely self-contained, weatherproof, four-channel monitoring system and cellular automatic voice dialer. Trigger events are announced via recorded voice message delivered by the cell phone when the call is answered.

Representing an exciting new level of achievement, the CVD-2020 combines technologically advanced features. ease of programming and reliable operation in a compact, unobtrusive dialer completely compatible with any security alarm system.

United Security Products, Inc. has supplied quality products to the security alarm industry for over 40 years, with proven performance in more than 100 million installations. Security systems dealers rely on USP for the most innovative products in the security industry. For your next installation, be sure to specify USP products.

## Models

- CVD-2020 your cell phone and service
- CVD-2020P comes with Cell Phone
- CVD-2020PS comes with Cell 1 year/400 minutes prepaid Cellular Service Included

# **Features**

- AT&T / Verizon Compatible Operates with Most Cellular Providers Worldwide - Bluetooth Capability
- Model PS Includes \$100 one year prepaid Cellular Service - No Contracts and No Monthly Fee
- 4 Separate Voice Dialer Channels/Zones
- **Built-in Line Seizure**
- Automatically Calls Up to 8 telephones, cell phones, etc.
- Can be used with landline Instantly switches to cellular calling if landline is cut
- Weatherproof NEMA cabinet
- EEPROM Memory retains programming if power is lost
- Includes Cell Phone and \$100 prepaid service -No Contracts and No Monthly Fee

# **Specifications**

Power source: 9-18VDC

Current (OPERATE mode - standby): 28mA typical. Current (OPERATE mode - dialing): 100mA max.

Activation:

- 1) N.C. Activation: dialer activates when an "open" is detected
- 2) N.O. Activation: dialer activates when a "close" is detected
- 3) Voltage Activation:

N.C. (applied voltage: Min. +5VDC, Max. +28VDC)

N.O. (loss of continuous voltage: Min. 0VDC, Max. 0.25VDC)

Max. Digits for outgoing numbers: 50

Operating temperature range: -18 to 55 C (0 to 130 F)

Dimensions (inches): 13.5x12x6.5"

Weight (ounces):9 Lbs Mounting: Wall or Flat Surface Case Material: Fiberglass

Color: Gray Warranty: 1 Year

