


## CX-1085 & CX-1085M PNEUMATIC TIMERS



**CX-1085**  
(Mounted to key switch.  
Sold separately)



**CX-1085M**  
(Mounted to push switch.  
Sold separately)

### FEATURES

- MAY BE ORDERED SEPARATELY OR ASSEMBLED WITH CAMDEN KEY SWITCHES OR PUSH BUTTONS
- ADJUSTABLE 1 TO 60 SECOND TIME DELAY
- DPST (FORM Z) CONTACTS
- 5 AMPS @ 24V DC CONTACTS
- HEAVY-DUTY CONSTRUCTION FOR LONG SERVICE LIFE

### DESCRIPTION

**Camden Door Controls CX-1085** pneumatic time delays require no power to operate. The timing range is 1 – 60 seconds, and is easily adjusted by a thumbscrew.

**Camden CX-1085 Pneumatic Timer** is integrated into the CM-1285, 2285, 3285/3585 and CM-1185/2085 Key Switches.

**Camden CX-1085M Pneumatic Timer** is integrated into the CM-4085/4185, 5085, 7085/7185 and CM-8085/8185 Push Buttons.

### APPLICATION

Camden pneumatic timers are ideal for use to de-activate magnetic locks where building codes mandate a non-electronic means of egress, or where power is not available for a conventional timer.

## SPECIFICATIONS

### CX-1085 & CX-1085M

DIMENSIONS:	CX-1085: 1" H x 1"W x 1 1/2"D (25mm x 25mm x 38mm)
	CX-1085M: 1" H x 1 3/8"W x 2"D (25mm x 35mm x 51mm)
OPERATING FORCE:	MAXIMUM 8 OZ.
SWITCH RATING:	5 AMPS @ 24V DC
TIME RANGE:	1 - 60 SEC. + - 15%
TEMPERATURE RANGE:	15° F TO 120 ° F (-9° C TO 49° C)
REPEAT ACCURACY:	+ - 10%
TIMER LIFE:	1,000,000 OPERATIONS

## ORDERING INFORMATION

MODEL	DESCRIPTION
CX-1085	PNEUMATIC TIMER FOR KEY SWITCHES
CX-1085M	PNEUMATIC TIMER FOR PUSH SWITCHES

