



D8223 Prox Pro Reader



The D8223 Prox Pro Reader provides Wiegand protocol interface capability in a black, easily mounted, weather-resistant enclosure.

Functions

Easy Mounting

The D8223 Prox Pro Reader is designed to fit a vertically-mounted, US standard, single-gang switch box for easy installation. It is field-adjustable through a selectable jumper setting so that it can be mounted directly to metal with minimal effect on its read range performance.

Beeper and LED Configurations can be Host and/or Locally Controlled

When a proximity card is presented to the reader, the red LED flashes green and the beeper sounds. Both the beeper and LED configurations can be controlled individually by the host system.

Indoor/outdoor Design

The rugged, weatherproof polycarbonate enclosure of the D8223 provides resistance to weather extremes and vandalism.

- ▶ **Easy mounting**
- ▶ **Beeper and LED configurations can be host and/or locally controlled**
- ▶ **Indoor/outdoor design**

Certifications and Approvals

Region	Certification
USA	UL ALVY: Access Control Systems Units (UL294), APOU: Proprietary Alarm Units (UL1076), UEHX7: Signaling Appliances, Miscellaneous Certified for Canada (cUL)

Installation/Configuration Notes

Compatibility Information

Credentials	D8236-10 Wiegand Proximity Card D8236KF-10 Wiegand Proximity Token D8236TG-10 Wiegand Proximity Adhesive Tag
Systems	ReadykeyPRO Readykey D9412G Control Panel D7412G Control Panel

Connection Considerations

The acceptable wire length from the door controller to the reader is up to 500 ft (152 m) when using 22 AWG (0.8 mm) cable.

Technical Specifications

Environmental

Relative Humidity	0% to 95%, non-condensing For UL Listed applications, 0% to 85%, non-condensing
Operating Temperature	-22°F to +150°F (-30°C to +65°C) For UL 294 applications, -22°F to +140°F (-30°C to +60°C)

Electrical

Current (Input)	100 mA average at 12 VDC; 120 mA peak at 24 VDC
Voltage (Input)	10 VDC to 28.5 VDC
Indicators	One LED that emits red or green light to display system status
Read Range	Up to 8 in. (20 cm)

Mechanical

Dimensions	5.0 in. x 5.0 in. x 1.0 in. (13 cm x 13 cm x 2.5 cm)
Weight	12 oz (0.3 kg)
Color	Charcoal gray
Material	Polycarbonate

Ordering Information

D8223 Prox Pro Reader	D8223
Provides Wiegand protocol interface capability in a black, easily mounted, weather-resistant enclosure.	

Accessories

D8236-10 Wiegand Proximity Card (26-bit)	D8236-10
Randomly-coded proximity card that is Wiegand 26-bit. Each package contains ten cards.	

D8236KF-10 Wiegand Proximity Token (26-bit)	D8236KF-10
Randomly-coded, gray, plastic, Wiegand 26-bit token. Attaches to a key chain. Each package contains ten tokens.	

D8236TG-10 Wiegand Proximity Adhesive Tag (26-bit)	D8236TG-10
Randomly-coded, gray, plastic, Wiegand 26-bit adhesive tag. Attaches to non-metallic surfaces. Each package contains ten tags.	

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6258 5511
Fax: +65 6571 2698
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by