



BOSCH
Invented for life

D9068 Fire Digital Alarm Communicator Transmitter (DACT)



- ▶ 12 VDC or 24 VDC operation
- ▶ Supports multiple reporting formats
- ▶ Five user-programmable input points (Class B, Style B)
- ▶ 100-event history buffer
- ▶ Dual phone line interface
- ▶ Program using the FMR-DACT-KEYPAD LCD Keypad or the D7033 LCD Remote Keypad
- ▶ Onboard Form C trouble relay
- ▶ LEDs for Heartbeat, System Trouble and Phone Line Trouble (one per line)
- ▶ Real-time clock

The D9068 Fire Communicator is a complete digital alarm communicator transmitter (DACT) for use with compatible fire alarm control panels (FACPs). Use dry contacts or open collector outputs for alarms and communications with the D9068.

Functions

Five Input Points

The D9068 supports five inputs that can be activated by dry contact relays or open collector outputs. Each of these inputs can be configured for one of seven types of conditions: Fire Alarm, Waterflow Alarm, Supervisory, Monitor Alarm, System Fault, AC Failure and Low Battery.

System Supervision

The D9068 is supervised with a hardware watchdog circuit. Failure of the control program results in a hardware reset within two seconds. The on-board trouble relay releases for the duration of the reset (the relay is normally held energized).

The D9068's EEPROM memory, input points, and phone lines are automatically tested periodically. The EEPROM checksum is verified every 10 minutes. If the EEPROM checksum fails, a trouble condition is locally annunciated and a trouble report sent.

Serial Data Input Dialing

The D9068 connects through the D9052 serial module to the D10024, D10024A, D9024, and D8024 analog FACPs, and transmits by point in all available formats.

User Interface

An FMR-DACT-KEYPAD LCD Keypad connects to a five-pin connector (option bus interface) and is used to program and troubleshoot the D9068. A D7033 Liquid-Crystal Display (LCD) Remote Keypad can also be used.

Reporting Formats

The D9068 supports five reporting formats: Modem IIIa², Contact ID, SIA110, SIA300, and 4/2.

Report Routing

There are six different report groups that can be routed to one of four phone settings. These report groups consist of non-supervisory alarms, supervisory alarms, alarm restorals, resets, supervisory restorals, tests and troubles, and trouble restorals.

Reset Report

A reset report is sent when the D9068 resets from any off-normal condition.

Phone Line Selection

The D9068 follows a pre-determined sequence to select between the phone lines. It also implements the new NFPA requirements for alternation of phone lines during test reporting. The D9068 maintains a variable that selects either Phone Line 1 or Phone Line 2 for automatic test reports. After each successful test report, the variable switches to select the other phone line.

Communication Failed Indication

The D9068 indicates a communication failure after ten attempts to communicate are completed without success. This causes the trouble output to activate and report the fault.

History Buffer

The D9068 has a history buffer that retains up to 100 events. Each event is tagged with the date and time of occurrence. This buffer can be viewed when an FMR-DACT-KEYPAD LCD Keypad (or a D7033 LCD Remote Keypad) is connected to the D9068. When the buffer is full, old events are discarded to make room for new events.

Lightning Suppression

MOVs and spark gaps suppress lightning surges and static discharges for inputs and telephone interface.

Certifications and Approvals

Region	Certification	
USA	UL	UOXX: Control Unit Accessories, System (UL864, 9th edition)
	FM	
	CSFM	7300-1615: 182 July 2008
	NYC-MEA	26-02-E, Vol. II
		26-02-E, Vol. III

Installation/Configuration Notes

Compatible Products

The following products are compatible with the D9068 Fire DACT:

Category	Product ID	Product Description
Control Panels	D7022	Conventional FACP
	D8024	Analog FACP
	D9024	Analog FACP
	D10024	Analog FACP
	D10024A	Analog FACP
Keypads and Annunciators	D7033	LCD keypad

Category	Product ID	Product Description
Modules	FMR-DACT-KEYPAD	LCD keypad
	D9052	Serial interface module

Parts Included

Quant.	Component
1	D9068 board
1	Metal enclosure (red)
1	Lightpipe
1	DCT-HWD hardware kit

Technical Specifications

Environmental Considerations

Environment:	Indoor, dry
Temperature (operating):	+32°F to +120°F (0°C to +49°C)

Mechanical Properties

Dimensions (HxWxD):	7.75 in. x 5.1 in. x 2.5 in. (19.7 cm x 13.1 cm x 6.4 cm)
Weight:	3.1 lb (1.4 kg)

Outputs

Trouble Relay:	One Form C relay onboard
Relay Rating:	1 A at 30 VDC

Power Requirements (use power-limited source)

Current (alarm):	190 mA maximum
Current (standby):	150 mA maximum
Voltage:	10.2 VDC to 28 VDC

Ordering Information

D9068 Fire Digital Alarm Communicator Transmitter (DACT) D9068

Complete digital alarm communicator transmitter (DACT) for use with compatible fire alarm control panels (FACPs)

Accessories

DCT-HWD Hardware Kit (DACT)

DACT hardware kit consisting of two RJ45 tel-co cable sets, five 2.2 kΩ EOL resistors, one wire power dialer, one dialer input wire harness, one dialer trouble relay harness, one wire dialer keypad, one ground wire, four PCB standoffs, and four mounting screws

DCT-HWD

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6258 5511
Fax: +65 6571 2698
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by