

# DS416 Single-Beam Photoelectric Detector

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ Single beam detection
- ▶ 10 m (30 ft) range
- ▶ Internally pointable optics
- ▶ AC/DC operation

The pole or surface mount DS416 Single Beam Photoelectric Detector is designed for indoor and outdoor applications. Consisting of a separate transmitter and receiver, it is designed to activate an alarm when an intruder passes within the direct line of sight between the transmitter and receiver. Its compact design makes it an ideal choice for short range outdoor applications.

## Functions

### Test Features

Red alarm LED activates upon detection. Green LEDs indicate normal operation.

## Certifications and approvals

Region	Certification
Europe	CE 89/336/EEC, EN50081-1: 1992 (EN55022: 1998, ClassB), EN50130-4: 1995 +A1: 1998, EN61000-4-2: 1995, EN61000-4-3: 1995, EN61000-4-4: 1995, EN61000-4-5: 1995, ENV50141: 1993
USA	UL ANSR: Intrusion Detection Units (UL639)

## Technical specifications

### Photobeam

Outdoor Range:	10 m (30 ft)
Beam:	Pulsed infrared; 950 nm, 1 kHz
Response Time:	100 ms minimum

### Environmental Considerations

Operating Temperature:	-20°C to +50°C (-4°F to +122°F)
------------------------	---------------------------------

### Mounting Considerations

Location:	Pole mount or surface mount
Pointability:	Coverage is adjustable $\pm 90^\circ$ horizontally, $\pm 5^\circ$ vertically.

### Enclosure Design

Dimensions:	14 cm x 8.6 cm x 10.7 cm (5.5 in. x 3.4 in. x 4.2 in.)
Material:	Smoked Lexan® housing.

## Power Requirements

Current Consumption (at 12 VDC):	Transmitter: 7 mA maximum Receiver: 25 mA maximum
Voltage:	10 VDC to 26 VDC; 8 VAC to 18.5 VAC.
Relay:	Form C alarm-activated contacts rated at 0.5 A maximum at 120 VAC; 1 A maximum at 24 VDC (resistive load).
Tamper:	Normally-closed with cover in place; rated 0.5 A at 30 V.

## Trademarks

Lexan® is either a trademark or registered trademark of General Electric Company in the United States and other countries.

## Ordering information

### DS416 Single-Beam Photoelectric Detector

Provides single beam detection and 10 m (30 ft) range.

Order number **DS416**

### Accessories

#### MP1 Metal Pole, 1 m (3 ft)

Straight metal poles measuring 1 m (3 ft) for pole mounting photoelectric detectors. Shipped in packages of two.

Order number **MP1**

#### MP2 Metal Pole, 1.2 m (4 ft)

Straight metal poles measuring 1.2 m (4 ft) for pole mounting photoelectric detectors. Shipped in packages of two.

Order number **MP2**

#### MP3 L-Curved Metal Pole

Curved metal poles for mounting to vertical surfaces for pole mounting photoelectric detectors. Shipped in packages of two.

Order number **MP3**

### Represented by:

#### Americas:

Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

#### Europe, Middle East, Africa:

Bosch Security Systems B.V.  
P.O. Box 80002  
5617 BA Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

#### Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia

#### China:

Bosch (Shanghai) Security Systems Ltd.  
201 Building, No. 333 Fuquan Road  
North IBP  
Changning District, Shanghai  
200335 China  
Phone +86 21 22181111  
Fax: +86 21 22182398  
www.boschsecurity.com.cn

#### America Latina:

Robert Bosch Ltda Security Systems Division  
Via Anhanguera, Km 98  
CEP 13065-900  
Campinas, Sao Paulo, Brazil  
Phone: +55 19 2103 2860  
Fax: +55 19 2103 2862  
latam.boschsecurity@bosch.com  
www.boschsecurity.com