

# DS422i and DS426i Dual-Beam Photoelectric Detectors

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ Dual beam detection
- ▶ Range up to 60 m (200 ft) outdoors, 180 m (600 ft) indoors
- ▶ Selectable response time
- ▶ Small unobtrusive design

The DS422i and DS426i are dual-beam photoelectric detectors designed for indoor and outdoor applications. Consisting of a separate transmitter and receiver, they are designed to activate an alarm when an intruder passes within the direct line of sight between the transmitter and receiver. The D422i has a range of 30 m (100 ft) outdoors or 90 m (300 ft) indoors. The D426i has a range of 60 m (200 ft) outdoors or 180 m (600 ft) indoors.

## Certifications and approvals

Region	Certification	
Europe	CE	
USA	UL	ANSR: Intrusion Detection Units (UL639)
China	CCC	2009031901000200

## Installation/configuration notes

### Mounting Considerations

Can be surface or pole mounted.

## Technical specifications

### Photobeam

DS422i Range	Indoor: 90 m (300 ft), Outdoor: 30 m (100 ft)
DS426i Range	Indoor: 180 m (600 ft), Outdoor: 60 m (200 ft)
Response Time:	Selectable from 50 ms to 700 ms

### Enclosure Design

Dimensions:	17.1 cm x 8.2 cm x 8.7 cm (6.75 in. x 3.25 in. x 3.5 in.)
Material:	Smoked Lexan®

### Environmental Considerations

Temperature (Operating):	-25°C to 55°C (-13°F to 130°F)
--------------------------	--------------------------------

### Mounting Considerations

Pointability:	Adjustable ±90° horizontally, ±24° vertically
---------------	---

## Outputs

Relay:	Alarm activated Form C with dry contacts rated at 0.5 A maximum at 30 VAC/VDC
Tamper:	Normally-closed with cover in place

## Power Requirements

DS422i Receiver Current Draw:	31 mA
DS426i Receiver Current Draw:	31 mA
DS422i Transmitter Current Draw:	10 mA
DS426i Transmitter Current Draw:	27 mA
Voltage (Input):	12 VDC to 28 VDC, non-polarized

## Trademarks

Lexan® is either a trademark or registered trademark of General Electric Company in the United States and other countries.

## Ordering information

### DS422i Photoelectric Detector

Provides an indoor range 90 m (300 ft), and an outdoor range of 30 m (100 ft).

Order number **DS422i**

### DS426i Photoelectric Detector

Provides an indoor range of 180 m (600 ft), and an outdoor range of 60 m (200 ft).

Order number **DS426i**

#### Represented by:

##### Americas:

Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

##### Europe, Middle East, Africa:

Bosch Security Systems B.V.  
P.O. Box 80002  
5617 BA Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

##### Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia

##### China:

Bosch (Shanghai) Security Systems Ltd.  
201 Building, No. 333 Fuquan Road  
North IBP  
Changning District, Shanghai  
200335 China  
Phone +86 21 22181111  
Fax: +86 21 22182398  
www.boschsecurity.com.cn

##### America Latina:

Robert Bosch Ltda Security Systems Division  
Via Anhanguera, Km 98  
CEP 13065-900  
Campinas, Sao Paulo, Brazil  
Phone: +55 19 2103 2860  
Fax: +55 19 2103 2862  
latam.boschsecurity@bosch.com  
www.boschsecurity.com