

# EGS-750

## Entraguard™ Silver Telephone Entry System

### DATA SHEET

#### Standard Features for Telephone Entry

- Stand alone functionality or seamless integration with Keri's access control system and Doors.Net software for real access control and telephone entry integration
- Four line, large font, soft white supertwist LCD display, Lexan™ cover
- Three 80 character, programmable, scrolling pages for instructions and messages with automatic timed rotation
- 750 tenant capacity, customer does not pay for extra capacity
- Up to 6-digit directory code, up to 5-digit Entraguard ID codes (PINs), up to 15-digit telephone numbers
- Networkable to manage multiple doors via RS-485
- Time Zone restrictions for calling tenants and for PINs
- Links a visitor to the resident who allowed entry
- Telephone entry units and access control units can be combined on a single network for a total of 128 controller units
- Flexible connectivity: RS-232, Modem, TCP/IP
- Stores up to 3,640 events, manages up to 255 individual sites
- Weather and vandal resistant housing
- Programmable talk time, tone dialing, adjustable volume
- Quick disconnect terminals
- Two Mylar™ speakers with superior sound
- Heavy duty door and alarm relays, door forced open and door held open alarms
- Built-in surge protection, non volatile memory
- Powerful Doors.Net Access Control Software with full access control features: time zones, temporary users, online programming, operator security levels, multiple site management, and automatic configuration



The **Entraguard Silver** is the mid size offering in Keri's telephone entry product line. With a large-font, 4-line, scrolling display, the Silver has a 750 tenant capacity, enough to handle the large majority of projects. Designed for looks and durability, it comes in an attractive, weather resistant, 14-gauge brushed stainless steel enclosure. The Silver entry panel is available at a price well below competitive medium capacity systems on the market. A no-phone-line system is available as an option.

Like its sister products, the Entraguard Platinum and Titanium, the Silver provides the best telephone entry/access control marriage by letting the unit function as a node on a PXL controller network, putting both applications under the acclaimed Doors.Net software umbrella for a seamless integration of the two. Additionally, the Silver, like the Platinum, can contain a PXL-500 Tiger Controller and an SB-593 Satellite Expansion Board for up to two doors of built-in card access in the same housing. A walk-up package addresses the basic visitor and resident control for the main entrance to a building.

Each Entraguard Silver also has two extra relay outputs that can be used in a variety of ways including turning on a lobby light, unlocking an interior door, or providing access to two separate entrances by using tone commands from the tenant's location or based on an access granted decision. An on-board modem is also included for remote programming.



2305 Bering Drive • San Jose, California 95131  
408-435-8400 • Toll Free: 800-260-5265 • Fax: 408-577-1792


email: [sales@kerisys.com](mailto:sales@kerisys.com) • web: [www.kerisys.com](http://www.kerisys.com)

# EGS-750 Entraguard™ Silver Telephone Entry System

DATA SHEET, Page 2 of 2

## Access Control Features

- True, integrated access control with PXL-500 or NXT controllers - the Silver becomes part of a Keri access control network
- Simple, one button auto-configuration
- 32 time zones, 3 holiday schedules
- Unlimited access control groups
- Automatically expiring Entraguard IDs (PINs) and cards
- Time Zones on Entraguard IDs (PINs) and cards, as well as doors and gates
- Full reporting of events
- Direct door operation from PC
- Automatic lock and unlock of doors and gates
- Assignable inputs and outputs (when using an optional SB-593 on a PXL-500)
- Rollcall/track, muster
- Image capture and optional badge printing
- Remote online management of multiple sites
- System operator security levels with configurable privileges



## Special Telephone Entry Features

- Do not Disturb Call Feature - programmable for individual tenants
- Do not Display Name Feature - programmable on a per tenant basis
- Remote online management of multiple sites
- Ability to link visitors to the residents who allowed them entry
- Ability to update several units in one pass
- Pre-wired walk-up package

## ORDERING INFORMATION:

Part Number	Description
EGS-750HF	Entraguard Silver, 750 Users
<i>For pre-installed color camera, add "-CO" to the model number</i>	
EGS-WUPW	Entraguard Walk-Up Package (includes EGS-750, PXL-500GW, P-300, KDP-552, boxed and prewired)
EGS-WUPP	Entraguard Walk-Up Package (includes EGS-750, PXL-500GP, MS-3000, KDP-552, boxed and prewired)
EGH-12	Heater Kit for Entraguard Units
EGP-PL	Platinum/Silver Postal Lock Kit - Field Installation
EPS-58	Power Supply Kit for Entraguard Units
FMK-95	Recess Mount Kit for Platinum/Silver
HSE-95	Hood/Pedestal Mount Adapter for Platinum/Silver

## General Features:

- Surface or recess mount
- Weather and vandal resistant housing
- Postal lock provision
- Non-volatile memory
- Built-in surge protection plus surge protection kit
- Programmable talk time
- Door forced open and door held open alarms
- Tone dialing
- Alarm output relay
- Adjustable volume control
- Maintenance free LED lighting
- Two Mylar™ speakers with superior sound
- Quick disconnect terminals

## Specifications\*:

- Capacity: Up to 750 Tenants
- Outputs: Door Relay, Alarm Relay, 2 additional programmable relays
- Operating Temperature: +5° to 140° F (-15° to 60° C) with heater: -20° to 140° F (-29° to 60° C)
- Input Power: 12 VDC @ 1 A
- Current Draw: 750 mA
- Relay Contact Rating: 1 A @ 24 VDC
- Size: 13.88" H x 10.34" W x 3.5" D (35.3 cm x 26.3 cm x 8.9 cm)
- Weight: 12.30 lbs (6.09 kg)
- Material: 14 gauge stainless steel
- Warranty: 2 years
- Finish: Brushed Stainless Steel

## Options / Accessories:

- Camera
- Postal Lock
- Handset
- Hooded Enclosure / Pedestal Mount
- Recessed Wall Mount Kit
- Heater (for operation below 5° F/-15° C)
- No Phone Line System

*\* Specifications subject to change without notice.  
All trademarks are the property of their respective owners.*

*When using Entraguard products in a dial-up application, Keri requires the use of an approved modem. Please refer to the Recommended Peripherals list on the web site or contact Keri customer service.*



Presented By: