



PRODUCT FEATURES

- Installs in the door and frame edges
- Flexible steel shield protects wire bundles up to 5/16" thick
- Works with almost any type butt hinge, continuous hinges and some pivot hinges.
- Rounded mounting tabs
- MagnaCare Lifetime Replacement No Fault Warranty

PRODUCT OPTIONS

- EPT for standard hinges and pivot hinges less than 3/4" offset
- EPTL for extended length
- EPT-SC for swing clear hinges or pivot hinges with larger offset*
- EL- Models are ElectroLynx compatible including 12-22 AWG wires, ElectroLynx connectors

SPECIFICATIONS:

- UL 10C Listed
- CAN4-S104 Listed
- UL 634 Listed (EL-EPT/ EL-EPTL)
- ULC/ORD-C634 (EL- EPT/EL-EPTL)
- ANSI/SDI-BHMA A250.13 (+/- 60 PSF) Windstorm Listed

Dimensions:

EPT Housing
12-3/4" L x 7/8" W x 11/16" D

EPTL Housing
21-3/8" L x 7/8" W x 11/16" D

Interior flex shield
3/8" [9.5mm]

Shipping Weight:

EPT: 0.75lbs [0.34kg]

EPTL: 1.20lbs [0.54kg]

EPT-SC: 1.25lbs [0.57kg]

EL-EPT: 0.75lbs [0.34kg]

EL-EPTL: 1.20lbs [0.54kg]

EL-EPT-SC: 1.25lbs [0.57kg]

Finishes:

US26/625 - Bright Chrome plated

*Not for use with center pivot doors

EPT

Electrical Power Transfer

Concealed, Tamper Resistant, Flexible Power and Data Transfer

The EPT Electric Power Transfer provides concealed, secure power and data conduit between a frame and door, transmitting power to electrified locks, exit bars and more. Its durable stamped steel housing and flexible spring steel conduit make the EPT suitable for most types of swinging doors with butt or continuous hinges or pivot hinges up to 3/4" offset. The EPT-SC accommodates swing-clear hinges and most pivot hinges.*

» MODELS

| | PART # | Description |
|------------------|--------|--|
| EPT | | EPT - Standard Version |
| EPTL | | EPT - Long Version |
| EPT-SC | | EPT - Swing Clear, Standard Version |
| EL-EPT | | EPT - Standard Version, ElectroLynx |
| EL-EPTL | | EPT - Long Version, ElectroLynx |
| EL-EPT-SC | | EPT - Swing Clear, Standard Version, ElectroLynx |

